

Custom High Performance Cooling Solutions w/ maxiGRIP™ Attachment



*Image above is for illustration purpose only.

ATS Part#: **ATS-59009-C1-R0**
 Description: maxiGRIP™ HS Assembly, T412, BLACK-ANODIZED, 42.5MM COMP

Heat Sink Type: **maxiFLOW**
 Heat Sink Attachment: **maxiGRIP**
 Equivalent Part Number: **ATS-59009-C2-R0**


Features & Benefits

- **maxiFLOW™** design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- **maxiGRIP™** attachment applies steady, even pressure to the component and does not require holes in the PCB
- Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock and Unpackaged Drop Testing standards
- Comes pre-assembled with high performance thermal interface material
- Designed for flip-chip processors such as Freescale MPCs
- "Keep-Out" Requirements: An "Un-Populated" border zone of 5mm around the component is necessary to facilitate the Installation/Removal of the **maxiGRIP™**. Please refer to the **maxiGRIP™** Keep-Out Guidelines and **maxiGRIP™** Installation/Removal Instructions for further details.

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	3.20 °C/W	2.60 °C/W	2.10 °C/W	1.90 °C/W	1.70 °C/W	1.50 °C/W	1.40 °C/W
	Ducted Flow	1.80	n/a	n/a	n/a	n/a	n/a	n/a

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
 <p>*Image above is for illustration purpose only.</p>	62.0 mm	52.0 mm	13.0 mm	52.0 mm	T412	BLACK-ANODIZED
<p>Notes:</p> <ul style="list-style-type: none"> • Dimension B refers to component size • Dimension C is the heat sink height from the bottom of the base to the top of the fin field. • ATS-59009-C2-R0 is the exact heat sink assembly with an equivalent thermal interface material (Saint Gobain C675). • Thermal performance data are provided for reference only. Actual performance may vary by application. • ATS reserves the right to update or change its products without notice to improve the design or performance. • ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant. • Contact ATS to learn about custom options available. 						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.

© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA



ATS ADVANCED THERMAL SOLUTIONS, INC.
 Innovations in Thermal Management®