

GBPC12, 15, 25 AND 35 SERIES

GLASS PASSIVATED SINGLE-PHASE BRIDGE RECTIFIER

Reverse Voltage - 50 to 1000 Volts Current Voltage - 12.0 to 35.0 Amperes

GBPC - W Wire leads



GBPC - Standard



FEATURES

- ◆ The plastic package has Underwriters Laboratory Flammability Classification 94V-0
- ◆ This series is UL recognized under component index, file number E54214
- ◆ Integrally molded heatsink provides very low thermal resistance for maximum heat dissipation
- ◆ Universal 3-way terminals; snap-on, wire wrap-around, or P.C.B. mounting
- ◆ High forward surge current capabilities
- ◆ Glass passivated chip junctions
- ◆ Typical I_R less than $0.3\mu A$
- ◆ High temperature soldering guaranteed:
260°C/10 seconds at 5lbs. (2.3 kg) tension

MECHANICAL DATA

Case: Molded plastic with heatsink integrally mounted in the bridge encapsulation
Terminals: Either plated 0.25" (6.35mm). Faston lugs or plated copper leads 0.040" (1.02mm) diameter. Suffix letter "W" added to indicate leads (e.g. GBPC12005W).
Mounting Position: See NOTE 3
Polarity: Polarity symbols molded on body
Mounting Torque: 20 in. - lb. max. **Weight:** 0.53 ounce, 15 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

GBPC12, 15, 25, 35

		SYMBOLS	005	01	02	04	06	08	10	UNITS
Maximum repetitive peak reverse voltage		V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage		V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage		V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum average forward rectified output current (SEE FIG. 1)		$I_{(AV)}$	GBPC12 12.0 GBPC15 15.0 GBPC25 25.0 GBPC35 35.0							Amps
Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method)		I_{FSM}	GBPC12 200.0 GBPC15 300.0 GBPC25 300.0 GBPC35 400.0							Amps
Rating (non-repetitive, for t greater than 1ms and less than 8.3ms) for fusing		I^2t	GBPC12 160.0 GBPC15 375.0 GBPC25 375.0 GBPC35 660.0							A ² sec
Maximum instantaneous forward voltage drop per leg at		V_F	GBPC12 $I_F=6.0A$ GBPC15 $I_F=7.5A$ GBPC25 $I_F=12.5A$ GBPC35 $I_F=17.5A$							Volts
Maximum reverse DC current at rated DC blocking voltage per leg		I_R	$T_A=25^\circ C$ 5.0 $T_A=125^\circ C$ 500.0							μA
RMS isolation voltage from case to leads		V_{ISO}	2500.0							Volts
Typical junction capacitance per leg (NOTE 1)		C_J	300.0							pF
Typical thermal resistance per leg (NOTE 2)		$R_{\theta JC}$	GBPC12-25 1.9 GBPC35 1.4							°C/W
Operating junction storage temperature range		T_J, T_{STG}	-55 to +150							°C

NOTES:

- (1) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts
- (2) Thermal resistance from junction to case per leg
- (3) Bolt down on heat-sink with silicone thermal compound between bridge and mounting surface for maximum heat transfer efficiency with #10 screw

RATINGS AND CHARACTERISTICS CURVES GBPC12, 15, 25 AND 35 SERIES

FIG. 1 - MAXIMUM OUTPUT RECTIFIED CURRENT




FIG. 2 - MAXIMUM OUTPUT RECTIFIED CURRENT




FIG. 3 - MAXIMUM POWER DISSIPATION





FIG. 4 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG



RATINGS AND CHARACTERISTICS CURVES GBPC12, 15, 25 AND 35 SERIES

FIG. 5 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER LEG




FIG. 6 - TYPICAL REVERSE LEAKAGE CHARACTERISTICS PER LEG




FIG. 7 - TYPICAL JUNCTION CAPACITANCE PER LEG




FIG. 8 - TYPICAL TRANSIENT THERMAL IMPEDANCE PER LEG




FIG. 9





FIG. 10



NOTES:

- (1) Corrosion resistant terminals designed with 0.25" female quick connectors for wrap or snap-on
- (2) A thin film of silicone thermal compound is recommended between the bridge case and mounting surface for improved thermal conduction