

2 Digits LED Numeric Displays

Ta=25°C

Type No.		Drawing No.	Peak Wave-length nm (Color)	Absolute Maximum Ratings					IF/seg Recommend.	Electro-Optical Characteristics				
Com. Anode	Com. Cathode			IF/seg	IR/seg	VF/seg	PD	Topr		VF Typ.	IF	Luminous Intensity Typ.	IF	IF Max.
				mA	mA	V	W	°C	mA	V	mA	μcd	mA	(VF=3V) μA
SL-1263	SL-1264	L-13	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	300	5	10
SL-2263	SL-2264	L-13	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	2000	15	10
SL-1263-20	SL-1264-20	L-14	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	300	5	10
SL-2263-20	SL-2264-20	L-14	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	2000	15	10
SL-1263-22	SL-1264-22	L-14	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	300	5	10
SL-2263-22	SL-2264-22	L-14	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	2000	15	10
SL-1273	SL-1274	L-15	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	300	5	10
SL-2273	SL-2274	L-15	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	2000	15	10
SL-1273-20	SL-1274-20	L-16	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	300	5	10
SL-2273-20	SL-2274-20	L-16	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	2000	15	10

Ta=25°C

Type No.		Drawing No.	Peak Wave-length nm (Color)	Absolute Maximum Ratings					IF/seg Recommend.	Electro-Optical Characteristics				
Com. Anode	Com. Cathode			IF/seg	IR/seg	VF/seg	PD	Topr		VF Typ.	IF	Luminous Intensity Typ.	IF	IF Max.
				mA	mA	V	W	°C	mA	V	mA	μcd	mA	(VF=3V) μA
SL-1283	SL-1284	L-17	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	350	5	10
SL-2283	SL-2284	L-17	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	800	15	10
SL-1283-20	SL-1284-20	L-18	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	350	5	10
SL-2283-20	SL-2284-20	L-18	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	800	15	10
SL-1283-22	SL-1284-22	L-18	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	350	5	10
SL-2283-22	SL-2284-22	L-18	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	800	15	10
SL-1283-24	SL-1284-24	L-19	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	350	5	10
SL-2283-24	SL-2284-24	L-19	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	800	15	10
SL-1283-27	SL-1284-27	L-19	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	350	5	10
SL-2283-27	SL-2284-27	L-19	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	800	15	10
SL-1203	SL-1204	L-20	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	300	5	10
SL-2203	SL-2204	L-20	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	2000	15	10

Ta=25°C

Type No.		Drawing No.	Peak Wave-length nm (Color)	Absolute Maximum Ratings					IF/seg Recommend.	Electro-Optical Characteristics				
Com. Anode	Com. Cathode			IF/seg	IR/seg	VF/seg	PD	Topr		VF Typ.	IF	Luminous Intensity Typ.	IF	IF Max.
				mA	mA	V	W	°C	mA	V	mA	μcd	mA	(VF=3V) μA
SL-1203-20	SL-1204-20	L-21	700 (R)	20	40	3	0.8	-25to70	3to10	1.9	5	300	5	10
SL-2203-20	SL-2204-20	L-21	565 (G)	20	40	3	0.8	-25to70	10to15	2.05	15	2000	15	10
SL-1225	SL-1226	L-22	700 (R)	20	40	3	1.4	-25to70	5to10	1.9	5	300	5	10
SL-2225	SL-2226	L-22	565 (G)	20	40	3	1.5	-25to70	10to15	2.05	15	700	15	10
SL-1255	SL-1256	L-23	700 (R)	20	40	3	0.65	-25to70	3to10	1.9	5	400	5	10
SL-2255	SL-2256	L-23	565 (G)	20	40	3	0.65	-25to70	10to15	2.05	15	1000	15	10
SL-1265-50	SL-1266-50	L-24	700 (R)	20	40	3	0.8	-25to70	5to10	1.9	5	300	5	10