

Specifications and Dimensions



KVA	PRIMARY 460V Delta SECONDARY 230Y/133 CATALOG NO.	PRIMARY 460V Delta SECONDARY 460Y/266 CATALOG NO.	APPROX. DIMENSIONS ① Inches (Cm.)			APPROX. SHIP WEIGHT Lbs. (Kg.)	TYPE MTG. W - Wall F - Floor	WEATHER SHIELD P/N	DESIGN FIGURE
			HEIGHT	WIDTH	DEPTH				
7.5	DTGA-7-2S or TS ④ (37)	DTGB-7-2S or TS ④ (34)	15.21 (38.6)	19.25 (48.9)	7.37 (18.7)	180 (81.6)	W	NA	F
11.0	DTGA-011-2S or TS ④ (37)	DTGB-011-2S or TS ④ (34)	18.86 (47.9)	20.30 (51.6)	9.03 (22.9)	265 (120.0)	F ①	NA	J
14.0	DTGA-014-2S or TS ④ (37)	DTGB-014-2S or TS ④ (34)	18.86 (47.9)	20.30 (51.6)	9.03 (22.9)	270 (123.0)	F ①	NA	J
20.0	DTGA-020-2S or TS ④ (37)	DTGB-020-2S or TS ④ (34)	20.77 (52.8)	20.94 (53.2)	10.18 (25.9)	435 (197.0)	F ①	NA	J
27.0	DTGA-027-4S (38)	DTGB-027-4S (35)	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	320 (145.0)	F ②	WS-A-1	E
34.0	DTGA-034-4S	DTGB-034-4S	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	340 (154.0)	F ②	WS-A-1	E
40.0	DTGA-040-4S	DTGB-040-4S	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	395 (179.0)	F ②	WS-A-1	E
51.0	DTGA-051-4S	DTGB-051-4S	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	400 (181.0)	F ②	WS-A-2	E
63.0	DTGA-063-4S	DTGB-063-4S	29.90 (75.9)	28.15 (71.5)	22.37 (56.8)	550 (250.0)	F ②	WS-A-2	E
75.0	DTGA-075-4S	DTGB-075-4S	29.90 (75.9)	28.15 (71.5)	22.37 (56.8)	570 (259.0)	F ②	WS-A-2	E
93.0	DTGA-093-4S	DTGB-093-4S	35.90 (91.2)	31.90 (81.0)	26.88 (68.3)	685 (311.0)	F	WS-A-3	E
118.0	DTGA-0118-4S	DTGB-0118-4S	35.90 (91.2)	31.90 (81.0)	26.88 (68.3)	765 (347.0)	F	WS-A-3	E
145.0	DTGA-0145-4S	DTGB-0145-4S	41.52 (105.5)	32.90 (83.6)	29.88 (75.9)	990 (449.0)	F	WS-A-4	E
175.0	DTGA-0175-4S	DTGB-0175-4S	41.52 (105.5)	32.90 (83.6)	29.88 (75.9)	1160 (526.0)	F	WS-A-4	E
220.0	DTGA-0220-4S	DTGB-0220-4S	41.52 (105.5)	32.90 (83.6)	29.88 (75.9)	1110 (504.0)	F	WS-A-4	E
275.0	DTGA-0275-4S ▼	DTGB-0275-4S ▼	45.60 (115.8)	39.50 (100.3)	35.50 (90.2)	2090 (948.0)	F	WS-A-5	E
330.0	DTGA-330-4S (39)	DTGB-330-4S (36)	52.00 (132.1)	52.00 (132.1)	40.00 (101.6)	2425 (1100.0)	F	WS-A-58	G
440.0	DTGA-440-4S	DTGB-440-4S	62.00 (157.5)	54.00 (137.2)	42.00 (106.7)	2625 (1191.0)	F	WS-B-3	G
550.0	DTGA-550-4S	DTGB-550-4S	64.00 (162.6)	60.00 (152.4)	42.00 (106.7)	3000 (1361.0)	F	WS-B-4	G
660.0	DTGA-660-4S ▼	DTGB-660-4S ▼	64.00 (162.6)	64.00 (162.6)	42.00 (106.7)	3700 (1678.0)	F	WS-B-5	G

KVA	PRIMARY 575V Delta SECONDARY 230Y/133 CATALOG NO.	PRIMARY 575V Delta SECONDARY 460Y/266 CATALOG NO.	APPROX. DIMENSIONS ① Inches (Cm.)			APPROX. SHIP WEIGHT Lbs. (Kg.)	TYPE MTG. W - Wall F - Floor	WEATHER SHIELD P/N	DESIGN FIGURE
			HEIGHT	WIDTH	DEPTH				
7.5	DTHA-7-2S or TS ④ (40)	DTHB-7-2S or TS ④ (43)	15.21 (38.6)	19.25 (48.9)	7.37 (18.7)	180 (81.6)	W	NA	F
11.0	DTHA-011-2S or TS ④ (40)	DTHB-011-2S or TS ④ (43)	18.86 (47.9)	20.30 (51.6)	9.03 (22.9)	265 (120.0)	F ①	NA	J
14.0	DTHA-014-2S or TS ④ (40)	DTHB-014-2S or TS ④ (43)	18.86 (47.9)	20.30 (51.6)	9.03 (22.9)	270 (123.0)	F ①	NA	J
20.0	DTHA-020-2S or TS ④ (40)	DTHB-020-2S or TS ④ (43)	20.77 (52.8)	20.94 (53.2)	10.18 (25.9)	435 (197.0)	F ①	NA	J
27.0	DTHA-027-4S (41)	DTHB-027-4S (44)	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	320 (145.0)	F ②	WS-A-1	E
34.0	DTHA-034-4S	DTHB-034-4S	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	340 (154.0)	F ②	WS-A-1	E
40.0	DTHA-040-4S	DTHB-040-4S	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	395 (179.0)	F ②	WS-A-1	E
51.0	DTHA-051-4S	DTHB-051-4S	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	400 (181.0)	F ②	WS-A-2	E
63.0	DTHA-063-4S	DTHB-063-4S	29.90 (75.9)	28.15 (71.5)	22.37 (56.8)	550 (250.0)	F ②	WS-A-2	E
75.0	DTHA-075-4S	DTHB-075-4S	29.90 (75.9)	28.15 (71.5)	22.37 (56.8)	570 (259.0)	F ②	WS-A-2	E
93.0	DTHA-093-4S	DTHB-093-4S	35.90 (91.2)	31.90 (81.0)	26.88 (68.3)	685 (311.0)	F	WS-A-3	E
118.0	DTHA-0118-4S	DTHB-0118-4S	35.90 (91.2)	31.90 (81.0)	26.88 (68.3)	765 (347.0)	F	WS-A-3	E
145.0	DTHA-0145-4S	DTHB-0145-4S	41.52 (105.5)	32.90 (83.6)	29.88 (75.9)	990 (449.0)	F	WS-A-4	E
175.0	DTHA-0175-4S	DTHB-0175-4S	41.52 (105.5)	32.90 (83.6)	29.88 (75.9)	1160 (526.0)	F	WS-A-4	E
220.0	DTHA-0220-4S	DTHB-0220-4S	41.52 (105.5)	32.90 (83.6)	29.88 (75.9)	1110 (504.0)	F	WS-A-4	E
275.0	DTHA-0275-4S ▼	DTHB-0275-4S ▼	45.60 (115.8)	39.50 (100.3)	35.50 (90.2)	2090 (948.0)	F	WS-A-5	E
330.0	DTHA-330-4S (42)	DTHB-330-4S (45)	52.00 (132.1)	52.00 (132.1)	40.00 (101.6)	2425 (1100.0)	F	WS-A-58	G
440.0	DTHA-440-4S	DTHB-440-4S	62.00 (157.5)	54.00 (137.2)	42.00 (106.7)	2625 (1191.0)	F	WS-B-3	G
550.0	DTHA-550-4S	DTHB-550-4S	64.00 (162.6)	60.00 (152.4)	42.00 (106.7)	3000 (1361.0)	F	WS-B-4	G
660.0	DTHA-660-4S ▼	DTHB-660-4S ▼	64.00 (162.6)	64.00 (162.6)	42.00 (106.7)	3700 (1678.0)	F	WS-B-5	G

① Optional wall mounting kits – part # PL 79911 refer to Page 50.

② Optional wall mounting kits – part # PL 79912 refer to Page 50.

③ Dimensions may change and are not to be used for detailed construction purposes. Please contact the factory for certified dimensional drawings.

④ For factory added thermal protection, 7.5 thru 20.0 KVA change suffix '-2S' to '-TS'.

The red () number following the catalog number is the electrical connection diagram number.