

# Ring Tongue Terminals

SA 1-800-800-0449






## Star Ring Terminals 22 to 14 Wire Range

The Star Ring is a serrated ring that is mainly used for grounding. Unlike a ring terminal, when you tighten down on a star ring, the "star blades", or serrated edges, actually pierce through paint or other coatings, and bite into the metal to insure a good connection or ground! The product may also eliminate the need for lock washers.

Steel Parts

Brass Parts



MATERIAL: BRASS OR STEEL

KRIMPTITE®





INSULKRIMP®  
(PVC INSULATION)

AVIKRIMP®  
(NYLON INSULATION)

Wire Range	Stud Size S	Max. Width W	Min. Clearance C	Part Number	Max. Length L	Part Number	Max. Length L	Part Number	Max. Length L
22-18 0.3-1.0mm <sup>2</sup> Brass	6	.385	.275	SRA-129-06	.70	SRA-229-06X	.93	SRA-829-06	.93
	8	.385	.275	SRA-129-08	.70	SRA-229-08X	.93	SRA-829-08	.93
	10	.385	.275	SRA-129-10	.70	SRA-229-10X	.93	SRA-829-10	.93
22-18 0.3-1.0mm <sup>2</sup> Steel	6	.385	.275	SRA-S-129-06	.70	SRA-S-229-06X	.93	SRA-S-829-06	.93
	8	.385	.275	SRA-S-129-08	.70	SRA-S-229-08X	.93	SRA-S-829-08	.93
	10	.385	.275	SRA-S-129-10	.70	SRA-S-229-10X	.93	SRA-S-829-10	.93
16-14 1.2-2.0mm <sup>2</sup> Brass	6	.385	.275	SRB-129-06	.70	SRB-229-06X	.93	SRB-829-06	.93
	8	.385	.275	SRB-129-08	.70	SRB-229-08X	.93	SRB-829-08	.93
	10	.385	.275	SRB-129-10	.70	SRB-229-10X	.93	SRB-829-10	.93
16-14 1.2-2.0mm <sup>2</sup> Steel	6	.385	.275	SRB-S-129-06	.70	SRB-S-229-06X	.93	SRB-S-829-06	.93
	8	.385	.275	SRB-S-129-08	.70	SRB-S-229-08X	.93	SRB-S-829-08	.93
	10	.385	.275	SRB-S-129-10	.70	SRB-S-229-10X	.93	SRB-S-829-10	.93

Note: For open barrel strip star rings, refer to page 22.

## Multi-Stud Rings 22 to 10 Wire Range



MATERIAL: COPPER

KRIMPTITE®

INSULKRIMP®  
(PVC INSULATION)

AVIKRIMP®  
(NYLON INSULATION)

Wire Range	Stud Size S	Max. Width W	Min. Clearance C	Part Number	Max. Length L	Part Number	Max. Length L	Part Number	Max. Length L
22-18 0.3-1.0mm <sup>2</sup>	6-8-10	.348	.447 .330	A-1006-MS	.866	A-2006-MSX	1.172	A-5006-MS	1.148
16-14 1.2-2.0mm <sup>2</sup>	6-8-10	.362	.447 .330	B-1006-MS	.866	B-2006-MSX	1.172	B-5006-MS	1.148
12-10 3.0-6.0mm <sup>2</sup>	6-8-10	.410	.447 .330	C-1006-MS	.890	C-2006-MSX	1.191	C-5006-MS	1.295

Note: For Terminals on Mylar Tape, add "T" at the end of loose piece part number.