



cable jacks, combi-head

for use as straight or right angle jacks



SUHNER TYPE	Ident. no.	Cable entries*	Weight	Notes
21 4195-50-0-10c	646502	Group D	67 g/2.35 oz.	inner conductor slot 2.55 mm/.100 in.

*fitting cable entries see page 8

cable jacks

SUHNER QUICK-FIT

stripping tools see page 11





fig. 1




fig. 2





fig. 3

SUHNER TYPE	Ident. no.	Suitable cables	Weight	Al	Fig.
21 4195-50-9-36c	650785	1/2" Superflex *: FSJ4-50B, HCF 1/2" Cu2Y AlCu	84 g/2.94 oz.	9152	1
21 4195-50-12-36c	650787	1/2" *: SUCOFEED 1/2", LDF4-50A, LCF 1/2" Cu2Y	100 g/3.50 oz.	9153	2
21 4195-50-23-1c	650789	7/8" *: SUCOFEED 7/8", LDF5-50A, LCF 7/8" Cu2Y	209 g/7.32 oz.	9154	3



* foam dielectric corrugated copper tube cable

bulkhead jack

outer conductor crimp D
inner conductor crimp 3



Mounting hole



SUHNER TYPE	Ident. no.	Suitable cables	Weight	Al	Notes
24 4195-50-7-1c	646305	RG 214/U	52 g/ 1.82 oz.	3061	VSWR ≤ 1.12; f ≤ 4.0 GHz