

SMA Male Plug to SMA Female Jack

Model Number

ADT-2593-MF-SMA-02


SPECIFICATIONS

Frequency: DC - 18.0 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



Note: Also available in 0.720 (18.2) O.A.L. as ADT-8000-22-SMA-02

SMA Female Jack to SMA Female Jack

Model Number

ADT-2595-FF-SMA-02


SPECIFICATIONS

Frequency: DC - 18.0 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



Note: Also available with knurled center section (0.875 O.A.L.) as ADT-2841-FF-SMA-02 and in 0.500 (12.7) O.A.L. with fully threaded barrel as ADT-8000-20-SMA-02 as shown in photograph.

SMA Male Plug to SMA Male Plug

Model Number

ADT-2594-MM-SMA-02


SPECIFICATIONS

Frequency: DC - 18.0 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



Note: Also available in 0.875 (22.2) O.A.L. as ADT-8000-21-SMA-02

SMA Female Jack to SMA Female Jack - Bulkhead Mount

Model Number

ADT-2823-FF-SMA-02


SPECIFICATIONS

Frequency: DC - 18.0 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



Formerly SMA-024-8000 and SMA-8000-24-000-02

Right Angle SMA Male Plug to SMA Female Jack

Model Number

ADT-8000-MF-SMA-02


SPECIFICATIONS

Frequency: DC - 18.0 GHz

VSWR: 1.05 + .010 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



Formerly SMA-028-8000 and SMA-8000-28-000-02

Right Angle SMA Female Jack to SMA Female Jack

Model Number

ADT-8000-FF-SMA-02


SPECIFICATIONS

Frequency: DC - 18.0 GHz

VSWR: 1.05 + .010 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



Formerly SMA-026-8000 and SMA-8000-26-000-02

Right Angle SMA Male Plug to SMA Male Plug

Model Number

ADT-8000-MM-SMA-02


SPECIFICATIONS

Frequency: DC - 18.0 GHz

VSWR: 1.05 + .010 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



SMA Female Jack to SMA Female Jack - Blkhd Mount - Hermetic

Model Number

ADT-2824-FF-SMA-02


SPECIFICATIONS

Frequency: DC - 18.0 GHz

VSWR: 1.10 + .010 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



Standard finish is passivated stainless steel, for gold plating change -02 suffix to -00.