

**.300 Ring  
.031 Electro-Tinned Copper  
16-14 AWG (Blue)**

**Spade and Ring Series  
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.147	.200	.250						
4	X			B	✓	✓	4000	50313	
		X		B	✓	✓	3000	50313-8	
			X	B	✓	*	3000	50313-8A	
	X			W	✓	✓	4000	50314	
		X		W	✓	✓	3000	50314-8	
			X	W	✓	*	3000	50314-8A	
6	X			B	✓	✓	4000	50325	
		X		B	✓	✓	3000	50325-8	
			X	B	✓	*	3000	50325-8A	
	X			W	✓	✓	4000	50326	
		X		W	✓	✓	3000	50326-8	
			X	W	✓	*	3000	50326-8A	
8	X			B	✓	✓	4000	50352	
		X		B	✓	✓	3000	50352-8	
			X	B	✓	*	3000	50352-8A	
	X			W	✓	✓	4000	50353	
		X		W	✓	✓	3000	50353-8	
			X	W	✓	*	3000	50353-8A	
10	X			B	✓	✓	4000	50364	
		X		B	✓	✓	3000	50364-8	
			X	B	✓	*	3000	50364-8A	
	X			W	✓	✓	4000	50365	
		X		W	✓	✓	3000	50365-8	
			X	W	✓	*	3000	50365-8A	

Recommended Strip Length  $\frac{9}{32} \pm \frac{1}{32}$   
\* Contact Factory for Latest Agency Approvals.

**S  
P  
A  
D  
E  
&  
R  
I  
N  
G**