




## DESCRIPTION

AMS8205A is the dual N-Channel enhancement mode power field effect transistor which is produced using high cell density, DMOS trench technology. This high density process is especially tailored to minimize on-state resistance. These devices are particularly suited for low voltage application, such as notebook computer power management and other battery powered circuits, where high-side switching is required.


## PIN CONFIGURATION TSSOP-8



**S : Subcontractor**  
**Y: Year**  
**A: Week Code**

## FEATURE

- 20V/6.0A,  $R_{DS(ON)} = 30\text{m-ohm}@V_{GS} = 4.5\text{V}$
- 20V/5.0A,  $R_{DS(ON)} = 42\text{m-ohm}@V_{GS} = 2.5\text{V}$
- Super high density cell design for extremely low  $R_{DS(ON)}$
- Exceptional low on-resistance and maximum DC current capability
- TSSOP-8 package design



## ORDERING INFORMATION

Part Number	Package	Part Marking
AMS8205A	TSSOP-8	SYA

Week Code Code : A ~ Z(1~26) ; a ~ z(27~52)

AMS8205A ST8 : TSSOP-8; R: Tape Reel ; G: Pb - Free

**ABSOLUTE MAXIMUM RATINGS** (Ta = 25°C Unless otherwise noted )

Parameter		Symbol		
Drain-Source Voltage		V <sub>DSS</sub>	20	V
Gate-Source Voltage		V <sub>GSS</sub>	+/-20	V
Continuous Drain Current (T <sub>J</sub> =150°C)	TA=25°C	I <sub>D</sub>	6.0	A
	TA=70°C		3.4	
Pulsed Drain Current		I <sub>DM</sub>	30	A
Continuous Source Current (Diode Conduction)		I <sub>S</sub>	2	A
Power Dissipation	TA=25°C	P <sub>D</sub>	2.0	W
	TA=70°C		1.2	
Operation Junction Temperature		T <sub>J</sub>	-40/140	°C
Storage Temperature Range		T <sub>STG</sub>	-55/150	°C
Thermal Resistance-Junction to Ambient		R <sub>θJA</sub>	105	°C/W







## ELECTRICAL CHARACTERISTICS ( Ta = 25°C Unless otherwise noted )

Parameter	Symbol	Condition	Min	Typ	Max	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	20			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	0.6		1.2	V
Gate Leakage Current	$I_{GSS}$	$V_{DS}=0V, V_{GS}=+/-20V$			$\pm 100$	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=20V, V_{GS}=0V$			1	uA
		$V_{DS}=20V, V_{GS}=0V$ $T_J=85^\circ C$			5	
On-State Drain Current	$I_{D(on)}$	$V_{DS} \leq 5V, V_{GS}=4.5V$	6			A
Drain-source On-Resistance	$R_{DS(on)}$	$V_{GS}=4.5V, I_D=6.0A$		0.024	0.030	$\Omega$
		$V_{GS}=2.5V, I_D=5.0A$		0.032	0.042	
Forward Transconductance	$g_{fs}$	$V_{DS}=5V, I_D=3.6A$		10		S
Diode Forward Voltage	$V_{SD}$	$I_S=1.7A, V_{GS}=0V$		0.8	1.2	V
<b>Dynamic</b>						
Total Gate Charge	$Q_g$	$V_{DS}=10V, V_{GS}=4.5V, V_{DS}=4A$		10.5		nC
Gate-Source Charge	$Q_{gs}$			2.5		
Gate-Drain Charge	$Q_{gd}$			2.1		
Input Capacitance	$C_{iss}$	$V_{DS}=8V, V_{GS}=0V$ $f=1MHz$		805		pF
Output Capacitance	$C_{oss}$			155		
Reverse Transfer Capacitance	$C_{rss}$			122		
Turn-On Time	$T_{d(on)}$	$V_{DD}=10V, R_L=10\Omega, I_D=1.0A,$ $V_{GEN}=4.5V, R_G=10\Omega$		14		nS
	$t_r$			6		
Turn-Off Time	$T_{d(off)}$			45		
	$t_f$			20		







## TYPICAL CHARACTERISTICS






## TYPICAL CHARACTERISTICS






## TYPICAL CHARACTERISTICS





## TSSOP-8 PACKAGE OUTLINE



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
D	2.900	3.100	0.114	0.122
E	4.300	4.500	0.169	0.177
b	0.190	0.300	0.007	0.012
c	0.090	0.200	0.004	0.008
E1	6.250	6.550	0.246	0.258
A		1.100		0.043
A2	0.800	1.000	0.031	0.039
A1	0.020	0.150	0.001	0.006
e	0.65 (BSC)		0.026 (BSC)	
L	0.500	0.700	0.020	0.028
H	0.25 (TYP)		0.01 (TYP)	
θ	1°	7°	1°	7°