

PMV117EN

μTrenchMOS™ enhanced logic level FET

Rev. 02 — 7 April 2005

Product data sheet

1. Product profile

1.1 General description

Logic level N-channel enhancement mode Field-Effect Transistor (FET) in a plastic package using TrenchMOS™ technology.

1.2 Features

- Logic level threshold
- Subminiature surface-mounted package
- Very fast switching

1.3 Applications



- Battery management
- High-speed switch
- Low power DC-to-DC converter

1.4 Quick reference data

- $V_{DS} \leq 30\text{ V}$
- $R_{DSon} \leq 117\text{ m}\Omega$ ($V_{GS} = 10\text{ V}$)
- $I_D \leq 2.5\text{ A}$
- $P_{tot} \leq 0.83\text{ W}$

2. Pinning information

Table 1: Pinning

Pin	Description	Simplified outline	Symbol
1	gate (G)	 <p>SOT23</p>	 <p>mbb076</p>
2	source (S)		
3	drain (D)		

3. Ordering information

Table 2: Ordering information

Type number	Package		
	Name	Description	Version
PMV117EN	TO-236AB	plastic surface mounted package; 3 leads	SOT23

4. Limiting values

Table 3: Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	drain-source voltage (DC)	$25\text{ °C} \leq T_j \leq 150\text{ °C}$	-	30	V
V_{DGR}	drain-gate voltage (DC)	$25\text{ °C} \leq T_j \leq 150\text{ °C}; R_{GS} = 20\text{ k}\Omega$	-	30	V
V_{GS}	gate-source voltage (DC)		-	± 20	V
I_D	drain current (DC)	$T_{sp} = 25\text{ °C}; V_{GS} = 10\text{ V};$ Figure 2 and 3	-	2.5	A
		$T_{sp} = 100\text{ °C}; V_{GS} = 10\text{ V};$ Figure 2	-	1.6	A
I_{DM}	peak drain current	$T_{sp} = 25\text{ °C};$ pulsed; $t_p \leq 10\text{ }\mu\text{s};$ Figure 3	-	10	A
P_{tot}	total power dissipation	$T_{sp} = 25\text{ °C};$ Figure 1	-	0.83	W
T_{stg}	storage temperature		-65	+150	°C
T_j	junction temperature		-65	+150	°C

Source-drain diode

I_S	source (diode forward) current (DC)	$T_{sp} = 25\text{ °C}$	-	0.8	A
I_{SM}	peak source (diode forward) current	$T_{sp} = 25\text{ °C};$ pulsed; $t_p \leq 10\text{ }\mu\text{s}$	-	3.3	A

5. Characteristics

Table 4: Characteristics

$T_j = 25\text{ °C}$ unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static characteristics						
$V_{(BR)DSS}$	drain-source breakdown voltage	$I_D = 10\text{ }\mu\text{A}$; $V_{GS} = 0\text{ V}$				
		$T_j = 25\text{ °C}$	30	37	-	V
		$T_j = -55\text{ °C}$	27	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	$I_D = 1\text{ mA}$; $V_{DS} = V_{GS}$; Figure 9 and 10				
		$T_j = 25\text{ °C}$	1.5	2	-	V
		$T_j = 150\text{ °C}$	1.1	-	-	V
		$T_j = -55\text{ °C}$	-	-	2.7	V
I_{DSS}	drain-source leakage current	$V_{DS} = 24\text{ V}$; $V_{GS} = 0\text{ V}$				
		$T_j = 25\text{ °C}$	-	0.01	0.5	μA
		$T_j = 150\text{ °C}$	-	-	10	μA
I_{GSS}	gate-source leakage current	$V_{GS} = \pm 20\text{ V}$; $V_{DS} = 0\text{ V}$	-	10	100	nA
$R_{DS(on)}$	drain-source on-state resistance	$V_{GS} = 10\text{ V}$; $I_D = 500\text{ mA}$; Figure 6 and 8				
		$T_j = 25\text{ °C}$	-	74	117	m Ω
		$V_{GS} = 4.5\text{ V}$; $I_D = 500\text{ mA}$; Figure 6 and 8	-			
		$T_j = 25\text{ °C}$	-	117	190	m Ω
		$T_j = 150\text{ °C}$		188	300	m Ω
Dynamic characteristics						
$Q_{g(tot)}$	total gate charge	$I_D = 0.5\text{ A}$; $V_{DD} = 15\text{ V}$; $V_{GS} = 10\text{ V}$; Figure 11	-	4.6	-	nC
Q_{gs}	gate-source charge		-	0.6	-	nC
Q_{gd}	gate-drain (Miller) charge		-	1.35	-	nC
C_{iss}	input capacitance	$V_{GS} = 0\text{ V}$; $V_{DS} = 10\text{ V}$; $f = 1\text{ MHz}$; Figure 13	-	147	-	pF
C_{oss}	output capacitance		-	65	-	pF
C_{rss}	reverse transfer capacitance		-	41	-	pF
$t_{d(on)}$	turn-on delay time	$V_{DD} = 15\text{ V}$; $R_L = 15\text{ }\Omega$; $V_{GS} = 10\text{ V}$	-	4	-	ns
t_r	rise time		-	7.5	-	ns
$t_{d(off)}$	turn-off delay time		-	18	-	ns
t_f	fall time		-	13	-	ns
Source-drain diode						
V_{SD}	source-drain (diode forward) voltage	$I_S = 0.83\text{ A}$; $V_{GS} = 0\text{ V}$; Figure 12	-	0.7	1.2	V
t_{rr}	reverse recovery time	$I_S = 1\text{ A}$; $dI_S/dt = -100\text{ A}/\mu\text{s}$; $V_{GS} = 0\text{ V}$; $V_{DS} = 25\text{ V}$	-	69	-	ns