

















FRONT VIEW	SIDE	MODEL	DESCRIPTION	1-4	DESCRIPTION
		Dual DB9 Feed-Thru Adaptor Sub Panel Two sided female entry allows a DB9 male terminated cable to be installed on each side of the adaptor. This not only saves time, but avoids potential assembly problems over the conventional D-Sub solder and crimp contact assembly. Each adaptor is fully populated to accept any type of wiring sequence.			FEMALE FEMALE  DB9
		USP2DB9F	2 DB9 Feed-Thru Adaptors	14.95	
		Dual DB15 Pin Feed-Thru Adaptor Sub Panels Two sided female entry allows a similar DB15 or HDB15 male terminated cables to be installed on each side of the adaptor. This system beats all other methods of terminating data cables on a panel. Fully populated to accept any type of wiring sequence. Your choice of standard D-Sub or High Density versions.			FEMALE FEMALE  DB15 HDB15
		USP2DB15F	2 DB15 Feed-Thru Adaptors	16.95	
		USP2HDB15F	2 HDB15 Feed-Thru Adaptors	20.95	
		Dual DB25 Feed-Thru Adaptor Sub Panel Two sided female entry allows a DB25 male terminated cable to be installed on each side of the adaptor. Six of these sub-panels mounted on one master rack panel will provide an excellent way to patch or program 12 incoming lines to 12 outgoing. Fully populated to accept any type of wiring sequence. Also available as a combination with a 9 pin and a 25 pin feed-thru mounted on one panel.			FEMALE FEMALE  DB25 DB9
		USP2DB25F	2 DB25 Feed-Thru Adaptors	18.95	
		USP-DB9-25F	One DB9 & One DB25 Feed-Thru	16.95	
		Single DB37 Feed-Thru Adaptor Sub Panel Two sided female entry allows a 37 pin D-Sub terminated cable to be installed on each side of the adaptor sub-panel. The adaptor is mounted on a 15° angle to allow panel opening clearance. This method of termination saves time and avoids potential assembly problems associated with conventional D-Sub solder and crimp contact assembly.			FEMALE FEMALE  DB37 15°
		USP-DB37F	One DB37 Feed-Thru Adaptor	13.95	
		DB25 (EIA232) 2-Position AB Rotary Switch Box This compact EIA232 switch box occupies two panel openings. The all metal construction offers optimum RFI/EMI shielding. Mounts with four machine screws, (supplied). Three DB25 female receptacles terminate in the rear. All 25 lines are switched for optimum usage. Rotary switching action connects line A or B to a common I/O. Four mounting feet provided for use on flat surface.			  B I/O A B I/O A
		USP-D25AB	2-Way EIA232 Sw. Box, A or B to I/O	79.95	

OEM / User Discounts: 5-9, 5%; 10-24, 10%; 25-99, 15%

