

VI TELEFILTER**Filter specification****TFS 63A****1/5****Measurement condition**

Ambient temperature:	23	°C
Input power level:	0	dBm
Terminating impedance: *		
Input:	410 Ω	-19,4 pF
Output:	370 Ω	-20,4 pF

Characteristics**Remark:**

The reference level for the relative attenuation a_{rel} of the TFS 63A is the minimum of the pass band attenuation. This value is defined as the insertion loss a_e . The nominal frequency f_N is fixed at 63,6 MHz without any tolerance. The values of relative attenuation a_{rel} are guaranteed for the whole operating temperature range. The frequency shift of the filter in the operating temperature range is included in the production tolerance scheme.

D a t a		typ. value		tolerance / limit		
Insertion loss (reference level)	$a_e = a_{min}$	9,8	dB	max.	12,0	dB
Nominal frequency	f_N	-			63,6	MHz
Centre frequency	f_C	63,6	MHz		-	
Passband	PB				$f_N \pm 0,25$	MHz
Pass band ripple		0,1	dB	max.	0,5	dB
Relative attenuation	a_{rel}					
f_N ... $f_N \pm 0,4$ MHz		0,2	dB	max.	0,5	dB
$f_N \pm 2,55$ MHz ... $f_N \pm 3,05$ MHz		47	dB	min.	40	dB
Group delay ripple within PB		75	ns	max.	500	ns
Operating temperature range	OTR	-			20 °C ... + 40 °C	
Storage temperature range		-			20 °C ... + 40 °C	
Temperature coefficient of frequency	TC_f^{**}	- 18	ppm/K			



*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.

**) $\Delta f(\text{Hz}) = TC_f(\text{ppm/K}) \times (T - T_0) \times f_{T0}(\text{MHz})$.


Generated:**Checked / Approved:**

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

VI TELEFILTER**Filter specification****TFS 63A****2/5****Filter characteristic****Construction and pin connection**


(All dimensions in mm)



- | | |
|---|------------------|
| 1 | Input |
| 2 | Input RF Return |
| 3 | Ground |
| 4 | Output RF Return |
| 5 | Output |
| 6 | Ground |
| 7 | Ground |
| 8 | Ground |

Date code: Year + week
 U 2006
 V 2007
 W 2008
 ...

The package is not hermetically sealed

50 Ohm Test circuit

Tele Filter GmbH
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
 E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

VI TELEFILTER**Filter specification****TFS 63A****3/5****Stability characteristics, reliability**

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 1 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5 g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max.;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;

This filter is RoHS compliant (2002/95/EG, 2005/618/EG)

Packing

Tape & Reel: IEC 286 – 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;


max. pieces of filters per reel:	900
reel of empty components at start:	min. 300 mm
reel of empty components at start including leader:	min. 500 mm
trailer:	min. 300 mm

Tape (all dimensions in mm)

W	: 24,00 ± 0,3
Po	: 4,00 ± 0,1
Do	: 1,50 +0,1/-0
E	: 1,75
F	: 11,50 ± 0,1
G(min)	: 0,60
P2	: 2,00 ± 0,1
P1	: 16,00 ± 0,1
D1(min)	: 1,50 ± 0,1
Ao	: 13,10 ± 0,1
Bo	: 17,60 ± 0,1
Ct	: 21,5

Reel (all dimensions in mm)

A	: 330
W1	: 24,4
W2(max)	: 30,4
N(min)	: 60
C	: 13,0




The minimum bending radius is 45 mm.

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

Conditions	Exposure
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile

VI TELEFILTER**Filter specification****TFS 63A****5/5****History**

Version	Reason of Changes	Name	Date
1.0	- Generation of development specification	Channaa	01.12.2005
1.1	- Change characteristics, data and construction	Strehl	16.01.2006
1.2	- terminating impedance (preliminary values), typical values, filter characteristics and matching configuration added - tape and reel corrected	Pfeiffer	18.01.2006
1.3	- terminating impedance corrected	Pfeiffer	28.02.2006

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.