

THREE PHASE



480 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS

KVA	CATALOG NO.	APPROX. DIMENSIONS ② (Inches)			APPROX. SHIP WEIGHT	TYPE MTG. W – Wall F – Floor	Weather Shield P/N	Electrical Connections and Design Figures Begin on Page 42
		HEIGHT	WIDTH	DEPTH				
15.0	NS10-0253311-3S	25.50	24.40	19.40	325	F ①	WS-A-1	22-E
30.0	NS10-0253312-3S	25.50	24.39	19.37	420	F ①	WS-A-1	22-E
45.0	NS10-0253313-3S	35.90	31.90	26.88	575	F ①	WS-A-3	22-E
75.0	NS10-0253314-3S	35.90	31.90	26.88	620	F	WS-A-3	22-E
112.5	NS10-0253315-3S	41.52	32.90	29.88	1200	F	WS-A-4	22-E
150.0	NS10-0253316-3S	41.52	32.90	29.88	1700	F	WS-A-4	22-E
225.0	NS10-253317-3S	52.00	56.00	40.00	2200	F	WS-A-60	23-G
300.0	NS10-253318-3S	62.00	64.00	42.00	2750	F	WS-B-3	23-G
500.0	NS10-253319-3S	86.00	72.00	60.00	4500	F	N/A	23-G

480 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS

KVA	CATALOG NO.	APPROX. DIMENSIONS ② (Inches)			APPROX. SHIP WEIGHT	TYPE MTG. W – Wall F – Floor	Weather Shield P/N	Electrical Connections and Design Figures Begin on Page 42
		HEIGHT	WIDTH	DEPTH				
15.0	NS75-0153311-3S	25.50	24.40	19.40	325	F ①	WS-A-1	22-E
30.0	NS75-0153312-3S	29.90	28.15	22.37	360	F ①	WS-A-2	22-E
45.0	NS75-0153313-3S	29.90	28.15	22.37	440	F ①	WS-A-3	22-E
75.0	NS75-0153314-3S	35.90	31.90	26.88	600	F	WS-A-3	22-E
112.5	NS75-0153315-3S	41.52	32.90	29.88	870	F	WS-A-4	22-E
150.0	NS75-0153316-3S	41.52	32.90	29.88	1500	F	WS-A-4	22-E
225.0	NS75-153317-3S	56.00	48.00	40.00	1800	F	WS-B-5	22-G
300.0	NS75-153318-3S	52.00	56.00	40.00	2500	F	WS-A-60	23-G
500.0	NS75-153319-3S	64.00	64.00	42.00	3790	F	WS-B-4	23-G

480 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS

KVA	CATALOG NO.	APPROX. DIMENSIONS ② (Inches)			APPROX. SHIP WEIGHT	TYPE MTG. W – Wall F – Floor	Weather Shield P/N	Electrical Connections and Design Figures Begin on Page 42
		HEIGHT	WIDTH	DEPTH				
15.0	NS25-0053311-3S	25.50	24.40	19.40	325	F ①	WS-A-1	22-E
30.0	NS25-0053312-3S	29.90	28.15	22.37	345	F ①	WS-A-2	22-E
45.0	NS25-0053313-3S	29.90	28.15	22.37	430	F ①	WS-A-2	22-E
75.0	NS25-0053314-3S	35.90	31.90	26.00	560	F	WS-A-3	22-E
112.5	NS25-0053315-3S	41.52	32.90	30.00	875	F	WS-A-4	22-E
150.0	NS25-0053316-3S	41.52	32.90	29.88	1475	F	WS-A-4	22-E
225.0	NS25-053317-3S	48.00	52.00	30.00	1785	F	WS-A-5	22-E
300.0	NS25-053318-3S	52.00	52.00	40.00	2300	F	WS-A-60	23-G
500.0	NS25-053319-3S	64.00	64.00	42.00	3790	F	WS-B-4	23-G

① Wall mounting brackets are available for these sizes, refer to page 50

② Dimensions in this section may change and are not to be used for detailed construction purposes. Please contact the factory for certified dimensional drawings.