

SKiIP 692 GAL 170 - 276 CTV


Absolute Maximum Ratings			
Symbol	Conditions ¹⁾	Values	Units
V _{isol} ⁴⁾	AC, 1min	4000	V
T _{op} , T _{stg}	Operating / stor. temperature	-25...+85	°C
IGBT and Diode			
V _{CES}		1700	V
V _{CC} ⁵⁾	Operating DC link voltage	1200	V
I _C	IGBT		A
T _j ³⁾	IGBT + Diode	-40...+150	°C
I _F	Diode		A
I _{FM}	Diode, t _p < 1 ms		A
I _{FSM}	Diode, T _j = 150 °C, 10ms; sin		A
I ² t (Diode)	Diode, T _j = 150 °C, 10ms	508	kAs ²
Driver			
V _{S1}	Stabilized Power Supply	18	V
V _{S2}	Non-stabilized Power Supply	30	V
f _{smax}	Switching frequency	10,0	kHz
dV/dt	Primary to secondary side	75	kV/μs

Characteristics					
Symbol	Conditions ¹⁾	min.	typ.	max.	Units
IGBT					
V _{(BR)CES}	Driver without supply	≥V _{CES}	-	-	V
I _{CES}	V _{GE} = 0, T _j = 25 °C	-	2	-	mA
	V _{CE} = V _{CES} , T _j = 125 °C	-	70	-	mA
V _{TO}	T _j = 125 °C	-	1,77	-	V
r _T	T _j = 125 °C	-	6,9	-	mΩ
V _{Cesat}	I _C = 600A, T _j = 125 °C	-	5,9	-	V
V _{Cesat}	I _C = 600A, T _j = 25 °C	-	3,85	-	V
E _{on} + E _{off}	V _{CC} =900/1200V, I _C =600A T _j = 125 °C	-	507/781	-	mJ
C _{CHC}	per Phase, AC side	-	1,6	-	nF
L _{CCE}	Top, Bottom	-	7,5	-	nH
FWD Diode ²⁾					
V _F = V _{EC}	I _F = 600A; T _j = 125 °C	-	1,59	-	V
V _F = V _{EC}	I _F = 600A; T _j = 25 °C	-	-	2,80	V
E _{on} + E _{off}	I _F = 600A; T _j = 125 °C	-	72	-	mJ
V _{TO}	T _j = 125 °C	-	0,90	-	V
r _T	T _j = 125 °C	-	1,2	-	mΩ
Thermal Characteristics					
R _{thjs} ¹⁰⁾	per IGBT	-	-	0,038	°C/W
R _{thjs} ¹⁰⁾	per Diode	-	-	0,054	°C/W
R _{thsa} ^{6,10)}	P16 heatsink; see case S2	-	-	0,044	°C/W
Driver					
I _{S1}	Supply current 15V-supply	250+530*f _s /f _{smax} +1,3*I _{AC} /A			mA
I _{S2}	Supply current 24V-supply	210+370*f _s /f _{smax} +1,0*I _{AC} /A			mA
t _{interlock-driver}	Interlock-time	-			μs
SKiIPPACK protection					
I _{TRIPSC}	Short circuit protection	750 ± 2%			A
I _{TRIPLG}	Ground fault protection	-			A
T _{TRIP}	Over-temp. protection	115 ± 5%			°C
U _{DCTRIP} ⁹⁾	U _{DC} -protection	1225 ± 2%			V
Mechanical Data					
M1	DC terminals, SI Units	4	-	6	Nm
M2	AC terminals, SI Units	8	-	10	Nm

SKiIPPACK®

SK integrated intelligent Power PACK boost converter SKiIP 692 GAL 170 - 276 CTV ^{7,9)}

Preliminary Data
Case S2



Features

- Short circuit protection, due to evaluation of current sensor signals
- Isolated power supply
- Low thermal impedance
- Optimal thermal management with integrated heatsink
- Pressure contact technology with increased power cycling capability, compact design
- Low stray inductance
- High power, small losses
- Over-temperature protection

- 1) T_{heatsink} = 25 °C, unless otherwise specified
- 2) CAL = Controlled Axial Lifetime Technology (soft and fast) without driver
- 3) Driver Input to Power Input/ Power Output to Heatsink with Semikron-DC link (low inductance)
- 4) other heatsinks on request
- 5) T - Temperature protection
- 6) V - 15 V or 24 V power supply
- 7) AC connection busbars must be connected by the user; copper busbars available on request
- 8) options available for driver: U - DC link voltage sense, F - Fiber optic connector
- 9) "s" referenced to temperature sensor