

Electrical Characteristics (At Ta=25°C, Unless Otherwise Specified)										
Type No.	I _R max (μA)	at V _R (V)	P _D min (W)	P _{IV} max (V)	V _F max (V)	@ I _F (mA)	C _d at V _R =0 (pF)	I _{FM} (mA)	trr (nsec)	
CT40	0.1	20	0.5	25	1	10	4	225	4	
CT41	0.1	30	0.5	40	1	10	4	225	4	
CT42	0.1	40	0.5	50	1	10	4	225	4	
CT43	5	50	0.5	75	1	10	4	225	4	
CT44	5	75	0.5	100	1	10	4	225	4	
CT45	0.1	20	0.5	25	1	20	4	225	4	
CT46	0.1	30	0.5	40	1	20	4	225	4	
CT47	0.1	40	0.5	50	1	20	4	225	4	
CT48	5	50	0.5	75	1	20	4	225	4	
CT49	5	75	0.5	100	1	20	4	225	4	
CT50	0.1	20	0.5	52	1	10	2	225	4	
CT51	0.1	30	0.5	40	1	10	2	225	4	
CT52	0.1	40	0.5	50	1	10	2	225	4	
CT53	5	50	0.5	75	1	10	2	225	4	
CT54	5	75	0.5	100	1	10	2	225	4	
CT55	0.1	20	0.5	25	1	20	2	225	4	
CT56	0.1	30	0.5	40	1	20	2	225	4	
CT57	0.1	40	0.5	50	1	20	2	225	4	
CT58	5	50	0.5	75	1	20	2	225	4	
CT59	5	75	0.5	100	1	20	2	225	4	
CT70	0.1	20	0.5	25	1	50	2	225	4	
CT71	0.1	30	0.5	40	1	50	2	225	4	
CT72	5	40	0.5	50	1	50	2	225	4	
CT73	5	50	0.5	75	1	50	2	225	4	
CT74	5	75	0.5	100	1	50	2	225	4	
CT75	0.1	20	0.5	25	1	100	2	225	4	
CT76	0.1	30	0.5	40	1	100	2	225	4	
CT77	0.1	40	0.5	50	1	100	2	225	4	
CT78	5	50	0.5	75	1	100	2	225	4	
CT79	5	75	0.5	100	1	100	2	225	4	
CT90	100	15	0.5		1	5	5 (min) 25 (max)			