

4

3

DWG NO. LMT101-1 SH 1 REV. N/C

1

This print and associated documents and the contained information are the confidential property of ELECTRONIC CABLE SPECIALISTS. Disclosure of, and/or reproduction of, all or part thereof or manufacture of any part from information contained on this print not specifically permitted by ELECTRONIC CABLE SPECIALISTS in writing is forbidden.

REVISIONS					
ECN	ZONE	REV.	DESCRIPTION	DATE	APPROVED
14282		N/C	NEW RELEASE	9/10/01	<i>[Signature]</i>

SPECIFICATIONS

ELECTRICAL

IMPEDANCE: 50 OHMS NOMINAL
FREQUENCY RANGE: 0 TO 6 GHz
VSWR: 1.70:1 MAXIMUM DC TO 6 GHz
INSERTION LOSS: .5 dB MAXIMUM @ 6 GHz
WORKING VOLTAGE: 500 VRMS @ SEA LEVEL
DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS @ SEA LEVEL
INSULATION RESISTANCE: 5000 MEGOHMS MINIMUM @ 500 VOLTS DC

MECHANICAL

CONNECTOR INTERFACE: DIMENSIONS PER MIL-STD-348, FIGURE 313-2 (TNC) AND ARINC 600, FIGURE 19-54.2 (SIZE 1)

ENVIRONMENTAL


TEMPERATURE RATING: -65°C TO +165°C
VIBRATION: MIL-STD-202, METHOD 204, COND. B
SHOCK: MIL-STD-202, METHOD 213, COND. I
THERMAL SHOCK: MIL-STD-202, METHOD 107 COND. B
CORROSION: MIL-STD-202, METHOD 101 COND. B
MOISTURE RESISTANCE: MIL-STD-202, METHOD 106

MATERIALS

BODY: BRASS PER ASTM B16
CENTER CONTACT: COPPER BERYLLIUM PER ASTM B196
DIELECTRIC: TEFLON PER ASTM D1710

FINISHES

BODY: GOLD PER MIL-G-45204
CENTER CONTACT: GOLD PER MIL-G-45204



SPRING



RETAINING RING

NOTES

1. DIMENSIONS ARE FOR REFERENCE ONLY.

ALL LENGTHS IN INCHES		ELECTRONIC CABLE SPECIALISTS FRANKLIN, WI 53132 PHONE: (414) 421-5300	
APPROVALS	DATE	TITLE: CUSTOMER SPECIFICATION	
E. FOSSELL	8/23/01	ARINC 404 SIZE 1 TO TNC JACK 50 OHM RF ADAPETR	
CHECKED BY: <i>C. Chapman</i>	9/10/01	SIZE	CAGE CODE
DESIGNED BY:		B	66197
PROJECT ENG:		LEVEL	PART NO.
ENG. MGR:		C	LMT101
		SCALE:	FILE NO
			SHEET: 1 OF 1

4

3

2

1