

## Features

- RoHS compliant\* versions available
- Overvoltage/lightning protection to ITU-T K.20/K.21/K.45
- Resettable overcurrent protection
- Typical application is secondary protection on telecom line cards

# 4B06B-514-RC - Surge Line Protection Module

## Electrical Characteristics

Resistance Value, 50 Ohm	
R1=R2=42 ohms .....	±1 %
Ratio Tolerance R1/R2 .....	±1 %
Resistance Value, 100 Ohm	
R1=R2=92 ohms .....	±1 %
Ratio Tolerance R1/R2 .....	±1 %
PPTC, R3 & R4, 8 Ohms Nominal Value	
Resistance Range .....	5 ohms to 15 ohms
Ratio Tolerance R3/R4 .....	Matched to within 1.0 ohms
Trip Time at 1 Amp .....	2 seconds at 25 °C
Hold Current .....	135 ma
Temperature Range .....	-40 °C to +85 °C


## Physical Characteristics

Body Style .....	Open Frame SIP
Substrate Material .....	96 % Alumina
Lead Frame Material .....	Copper, solder coated
Flammability .....	Conforms to UL94V-0

## Functional Characteristics


Lightning Surge Test .....	10 x 700 μs, 1.5 kV
Power Induction .....	600 V rms
Power Contact .....	230 V rms

## Product Dimensions



DIMENSIONS: MILLIMETERS  
(INCHES)

## Electrical Schematic



## How To Order

	<b>4B 06 B - 514 - XXX LF</b>
Model _____	(4B = Open Frame)
Number of Pins _____	
Physical Configuration _____	
Electrical Configuration _____	514 = Matched pair of resistors plus PPTC
Resistance Code _____	• 500 = 50 Ω • 101 = 100 Ω
RoHS Compliant Option _____	Blank = Standard Product LF = RoHS Compliant Product

**BOURNS®**

### Asia-Pacific:

TEL +886- (0)2 25624117  
FAX +886- (0)2 25624116

### Europe:

TEL +41-41 7685555  
FAX +41-41 7685510

### Americas:

TEL +1-951 781-5500  
FAX +1-951 781-5700

[www.bourns.com](http://www.bourns.com)