## **BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin**





Description: 40.00 x 40.00 x 6.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin



Heat Sink Type: Custom Pin Fin

Heat Sink Attachment: N/A Equivalent Part Number: N/A

\*Image above is for illustration purpose only.

## **Features & Benefits**

- · High efficiency pin fin design provides low pressure drop characteristics
- · Large surface area increases heat sink performance
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- · Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

## **Thermal Performance**

| AIR VELOCITY       |               | @200 LFM<br>1.0 M/S | @300 LFM<br>1.5 M/S | @400 LFM<br>2.0 M/S | @500 LFM<br>2.5 M/S | @600 LFM<br>3.0 M/S | @700 LFM<br>3.5 M/S | @800 LFM<br>4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 12.05 °C/W          | 8 °C/W              | 6.4 °C/W            | 5.5 °C/W            | 4.9 °C/W            | 4.5 °C/W            | 4.2 °C/W            |
|                    | Ducted Flow   | 4.6                 | 3.9                 | 3.5                 | 3.1                 | 2.9                 | 2.7                 | 2.6                 |

## **Product Detail**





