Reotop Mount

3 dB Gain, Bright DURA-CON™ and Black DURA-COAT™ High Performance Antennas

Models

DURA-CON Models ASP-1850 • ASP-1851 • ASP-1855 DURA-COAT Models ASP-1860 • ASP-1865

Rugged — one piece whip construction, including phasing coil **High Performance** — 5/8 wavelength upper whip plus 1/4 wavelength lower section produces 3 dBd (5 dBi) omnidirectional gain

Noise-Free — male-female contact in mount provides positive connection for noiseless duplex or telephone operation

Broadband — models cover entire specified band without tuning **Convenient** — whip is easily removed for waterproof car wash clearance

Electrical
Power 100 watts maximum

Gain 3 dBd (5 dBi)

Frequency Range 806-869 MHz (ASPA prefix) 890-960 MHz (ASPG1860 series)

VSWR 1.5:1 Impedance 50 ohms

Pattern Omnidirectional when roof mounted; ground

plane required

Mechanical

Whip Material Stainless steel DURA-CON plated or black

DURA-COAT

Base and Fittings Aluminum, brass and plated steel

Cable 17 ft (5.2 m) PRO-FLEX^M (where supplied)

Connector See table (crimp tool required for most connectors)

Overall Length Approximately 14 inches (36 cm)

Antenna Mounting Options

ASPA1851N

3/4 inch hole rooftop mount, PRO-FLEX cable, plated whip and N male crimp connector.



Plated whip, conversion/ replacement antenna only; no mount or cable.

MA

ASPA1860 Series


3/4 inch hole rooftop mount, PRO-FLEX cable, black whip.

ASPA1865

Black whip, conversion/ replacement antenna only; no mount or cable.



Mount & Cable	Connector				No
	Style	Mini-UHF Male	N Male	TNC Male	Connector or Cable
3/4 inch Hole Mount	DURA-CON Plated	ASPA1850M	ASPA1850N (clamp) ASPA1851N (crimp)	ASPA1850T	
	DURA-COAT Black	ASPA1860M ASPG1860M	ASPA1860N ASPG1860N	ASPA1860T ASPG1860T	
Conversion Antenna No Mount or Cable	DURA-CON Plated				ASPA1855
	DURA-COAT Black				ASPA1865 ASPG1865



ASPA1850 Series 3/4 inch hole rooftop mount, PRO-FLEX cable, plated whip.

