


# TVS/ESD Arrays

RLSO10A055LV Series

## TVS/ESD Arrays - RLSO10A055LV Series

### Features

- ESD protection for high-speed data lines to
- IEC 61000-4-2 (ESD)  $\pm 18\text{kV}$  (air),  $\pm 12\text{kV}$  (contact)
- IEC 61000-4-5 (Lightning) 5A (8/20 $\mu\text{s}$ )
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- Array of surge rated diodes with internal TVS Diode
- Small package saves board space
- Protects four I/O lines and one Vcc line
- Low capacitance: 0.3pF typical (I/O to I/O)
- Low clamping voltage
- Low operating voltage: 5.0V
- Solid-state silicon-avalanche technology



### Mechanical Characteristics

- JEDEC MSOP 10L package
- Molding compound flammability rating: UL 94V-0
- Marking : Marking code and date code
- Packaging : Tape and Reel per EIA 481
- Lead Finish: Matte Tin
- RoHS/WEEE Compliant


### Applications

- High Definition Multi-Media Interface (HDMI)
- Digital Visual Interface (DVI)
- 10/100/1000 Ethernet
- Monitors and Flat Panel Displays
- Notebook Computers
- Set Top Box
- Projection TV

### Life Support Note

- Not Intended for Use in Life Support or Life Saving Applications
- The products shown herein are not designed for use in life sustaining or life saving applications unless otherwise expressly indicated

### Pinout and Functional Block Diagram



## TVS/ESD Arrays - RLSO10A055LV Series

### Absolute Maximum Rating

Rating	Symbol	Value	Units
Peak pulse power (tp=8/20 s waveform)	P <sub>pp</sub>	125	Watts
ESD voltage (HBM contact)	V <sub>ESD</sub>	±8	A
ESD voltage (AIR contact)	V <sub>ESD</sub>	±15	Kv
Operating Temperature	T <sub>J</sub>	-55~+150	°C
Storage Temperature	T <sub>STG</sub>	-55~+150	°C


### Electrical Characteristics Per Lin (@ 25°C Unless Otherwise Specified)

Parameter	Symbol	Conditions	Minimum	Typical	Maximum	Units
Reverse Stand-Off Voltage	V <sub>RWM</sub>	Pin 3 to 8	-	-	5	V
Reverse breakdown voltage	V <sub>BR</sub>	I <sub>t</sub> = 1mA Pin 3 to 8	6.0	-	-	V
Reverse Leakage Current	I <sub>R</sub>	V <sub>RWM</sub> = 5V, T=25°C Pin 3 to 8	-	-	1	µA
Clamping voltage (tp=8/20s)	V <sub>C</sub>	I <sub>PP</sub> = 1A, tp = 8/20µs Any I/O pin to ground	-	-	15	V
Clamping voltage (tp=8/20s)	V <sub>C</sub>	I <sub>PP</sub> = 5A, tp = 8/20µs Any I/O pin to ground	-	-	20	V
Junction Capacitance	V <sub>C</sub>	V <sub>R</sub> = 0V, f = 1MHz Between I/O pins	-	0.3	0.7	pF
Junction Capacitance	V <sub>C</sub>	V <sub>R</sub> = 0V, f = 1MHz Any I/O pin to ground	-	0.7	0.9	pF


## TVS/ESD Arrays - RLSO10A055LV Series

### Typical Characteristics


**Non-Repetitive Peak Pulse Power vs. Pulse Time**




**Power Derating Curve**




**Pulse Waveform**




**Clamping Voltage vs. Peak Pulse Current**



**Forward Voltage vs. Forward Current**




**Normalized Capacitance vs. Reverse Voltage**



## TVS/ESD Arrays - RLSO10A055LV Series


### Package dimension MSOP-10



Dimensions						
DIM	Inches			Millimeters		
	Min	Nom	Max	Min	Nom	Max
A	-	-	.043	-	-	1.10
A1	.000	-	.006	0.00	-	0.15
A2	.030	-	.037	0.75	-	0.95
b	.007	-	.011	0.17	-	0.27
c	.003	-	.009	0.08	-	0.23
D	.114	.118	.122	2.90	3.00	3.10
E1	.114	.118	.122	2.90	3.00	3.10
E	.193BSC			4.90BSC		
e	.020BSC			0.50BSC		
L	.016	.024	0.32	0.40	0.60	0.80
L1	(.037)			(.95)		
N	10			10		
aaa	.004			0.10		
bbb	.003			0.08		
ccc	.010			0.25		


## TVS/ESD Arrays - RLSO10A055LV Series

### Soldering footprint



DIMENSIONS		
DIM	INCHES	MILLIMETERS
C	(.161)	(4.10)
G	.98	2.50
P	.020	0.50
X	.011	0.30
Y	.063	1.60
Z	.224	5.70

### Part Number Code



### Ordering Information

Part Number	Package	Min. Order Qty.
RLSO10A055LV	MSOP-10	3000pcs

### Warehouse Storage Conditions of Products

Storage Conditions:

1. Storage Temperature: -10°C~+40°C
2. Relative Humidity: ≤75%RH
3. Keep away from corrosive atmosphere and sunlight.
4. Period of Storage: 1 year

## RuiLongYuan Electronics Co., Ltd.

---

- Reproducing and modifying information of the document is prohibited without permission from Ruilongyuan International Inc.
- Ruilongyuan International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Ruilongyuan International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Ruilongyuan International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Ruilongyuan International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Ruilongyuan International Inc. for any damages resulting from such improper use or sale.

---

**Tel: +86-755-8290 8296**

**Fax: +86-755-8290 8002**

**E-mail: jack@ruilon.com**