



CSB100-550-4COM

Slim Type for IBASE IB550F 3.5" Disk-Size SBC

SBC System

CSB100-550

Slim Type for IBASE IB550F 3.5" Disk-Size SBC

SBC System



Features

- Onboard AMD Geode™ LX800 Processor, 500MHz
- Slim box fanless design for a wide variety of applications
- Supports 4 x COM ports
- One 2.5" SATA HDD
- Available in black coating color
- Wall mount kit included

Specifications

System Mainboard	IB550F
CPU Type	AMD Geode™ LX800
System Speed	500MHz
Memory	1GB DDR SO-DIMM
Construction	SECC
Chassis Color	Black
Front Panel External I/O	Front Audio(MIC-in, Line-in , Line out), 2 x USB ports, Power switch
Rear Panel External I/O	2x USB ports, 1x RJ-45 , 1x VGA , 4x COM ports, KBMS, DC-in jack
Storage	1x 2.5" HDD
Power Supply	60W power adaptor
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	172.4mm(W) x 125mm(D) x 47.4mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C ~ 80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	CFD: 5 grms / 5~500Hz / random operation HDD: 1g / 5~500Hz / random operation

Ordering Information

CSB100-550-4COM	Steel chassis for IB550F 3.5" SBC, 2.5" 250GB SATA HDD , 1GB DDR memory, 60W power adaptor
-----------------	--

Features

- Onboard AMD Geode™ LX800 processor, 500MHz
- Fanless slim box design for a wide variety of applications
- One 2.5" 160GB SATA HDD
- Chassis available in black color
- Wall mount kit included

Specifications

System Mainboard	IB550F
CPU Type	AMD Geode™ LX800
System Speed	500MHz
Memory	1x DDR2 SO-DIMM
Construction	SECC
Chassis Color	Black
Front Panel External I/O	Front audio, Power switch
Rear Panel External I/O	2x USB ports, 1x VGA connector, 1x COM ports, 1x RJ-45 connector, KB/MS connector, DC-in Jack
Storage	1x 2.5" 160GB HDD
Power Supply	60W power adaptor
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	172.4mm(W) x 125mm(D) x 52.4mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

Ordering Information

CSB100-550	Steel Chassis with IB550F 3.5" SBC, 2.5" 250GB SATA HDD, 60W power adaptor
------------	--

- 01 Motherboards
- 02 Disk-Size SBCs
- 03 CPU Modules
- 04 PC 104 Plus
- 05 CPU Cards
- 06 RISC SBCs
- 07 Embedded Systems