
A5 SERIES PCB.TO.PCB CONNECTORS

Scope

A5 series are low cost version of HIF3H series.




Features

- 1. A5 series sockets provide mating compatibility with HIROSE A1, HIF3E and HIF3H series pin headers.
- 2. No flux protection
- 3. Low cost products by massproduction.

Application

Various office automation equipment

Ordering Information




Material & Finish

Insulator	PCB resin, black, UL94V-0
Contact	Copper alloy, Selective gold plating + Nickel plating

Electric Performance

Current Rating	1A		
Rated voltage	AC300V		
Insulation Resistance	Min. 1000M ohm @DC500V		
Withstand Voltage	AC1000V for 1 minute		
Contact Resistance	Max. 30m ohm at DC100mA		

Straight Type Receptacle



Par No	No. of Pins	Α	В
A5-10DA-2.5408A	10	13.7	10.16
_AE-16IZA-ZBADSA	16	21.32	17.78
AS-200A-2.54ESA	20	26.4	22.86
A5-26DA-2,64 0\$ A	26	34.02	30.48
A5-30DA-254D\$A	30	39.1	35.56
A5-34DA-2,54DSA	34	44.18	40.64
A5-40UA-254DBA	40	51.8	48.26
A6-500A-2,540\$A	50	64.5	60.96
A5-800A-25485A	60	77.2	73.66

Note 1: Stand-off numbers vary according to pin numbers.

Note 2: Polarizing slit varies according to products.