




DELTA P/N : MPT136-H1 Series

Mechanical dimensions



Unit : mm	
A'	13.45 ± 0.35
A	12.6 ± 0.2
B	5.8 ± 0.2
C	2.0 ± 0.5
C'	2.5 ± 0.1
D	5.0 ± 0.5
D'	6.0 ± 0.2
E	0~0.15
F	5.5
G	8.0
H	14.5

Electrical Characteristics

Part No.	Lo @0A (uH) ± 20%	Ir(Adc)	Isat(Adc)	DCR (mΩ)	
				TYP.	MAX
MPT136-8R2H1	8.2	11.0	13.5	13.6	16.0
MPT136-100H1	10.0	10.0	12.5	18.0	20.7
MPT136-120H1	12.0	7.0	10.0	20.0	23.0
MPT136-150H1	15.0	6.0	9.0	25.0	29.0
MPT136-180H1	18.0	5.0	8.0	30.0	35.0
MPT136-220H1	22.0	5.0	7.5	34.0	39.5
MPT136-270H1	27.0	4.0	6.5	49.0	56.0
MPT136-330H1	33.0	4.0	6.0	65.0	75.0
MPT136-470H1	47.0	3.5	5.5	80.0	90.0
MPT136-680H1	68.0	3.0	4.5	120.0	140.0
MPT136-101H1	100.0	2.5	3.5	180.0	200.0
MPT136-121H1	120.0	2.3	3.2	210.0	235.0
MPT136-151H1	150.0	2.0	2.7	300.0	350.0

NOTES:

- (1) All test data is referenced to 25°C ambient.
- (2) Ir is the DC current which cause the surface temperature of the part increase approximate 40°C
- (3) Isat is the DC current which cause the inductance drop approximate 30% of Lo.
- (4) Operating temperature range -55°C to 125°C. (The part temperature should be kepted under 125°C when the worse operating condition apply on it. Circuit design, component placement, PWB tracesize and thickness, airflow and other cooling provision may affect the part temperature. Part temperature should be verified in the end application.)
- (5) The rated current is depended on Ir and Isat which one is lower.