

Type No.	Maximum Ratings								Electrical Characteristics (T _a =25°C, Unless Otherwise Specified)										
	V _{CB0} (V)	V _{CE0} (V)	V _{EB0} (V)	P _D (W)	I _C (A)	I _{CB0} (μA)	V _{CB} (V)	I _{CES} (μA)	V _{CE} (V)	h _{FE}	I _C & V _{CE} (A) (V)	V _{CE(SAT)} (V)	V _{BE(SAT)} (V)	I _C (A)	C _{ob} (pF)	f _i (MHz)	I _C (mA)		
	Min	Min	Min	@ T _c =25°C		Max	@ (V)	Max	@ (V)	Min	Max	Max	Min	Max	Max	Min	Typ	Max	
BU326	# 800	375	10	75	6			1000	800	**	25	1	5	1.5 3	1.4 1.6	2.5 4		6	200
BU326A	# 900	400	10	75	6			1000	900	**	25	1	5	1.5 3	1.4 1.6	2.5 4		6	200
BU608	400	200	6	90	7	100	330	\$5000	400					1.0	1.5	6	10		500
CDN055	50	50	5	50	5	200	50			25	100	2	2	1		2			
CSC1454	300	300	6	50	4	1000	300			20		1	5	1.5 3	1.4 1.6	2.5 4			
CSD200	1500	700	5	10	2.5	1000	1500	1000	1500	2.5		2	5	5	1.5	2			
CSD1168	1500	400	6	50	5			1000	1500	9	25	1	4	1	1.5	2			
CSD1168P	1500	800	5	50	5			1000	1500	9	18	1	4	1	1.5	2			
CSD1168Q	1500	800	5	50	5			1000	1500	15	25	1	4	1	1.5	2			

#NOTE: V_{CE(S)}
 ** : Typical Value
 \$: I_{CEV}