



MSSA1450R



Active

## Slide Switches

[Not ELV, RoHS, or ELV Compliant \(Find RoHS Compliant Alternates\)](#)

### Product Highlights:

- Number of Positions = 4
- Single Pole - Four Throw Configuration (Pole-Throw)
- Actuator Style = Extended, Side
- Actuator Color = Black
- MSSA Series

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

## Documentation & Additional Information

### Product Drawings:

- [SLIDE SWITCH](#) (PDF, English)

### Catalog Pages/Data Sheets:

- [ALCOSWITCH PRODUCTS](#) (PDF, English)

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files:

- None Available

### Additional Information:

- [Product Line Information](#)

### Related Products:

- [Tooling](#)

[List all Documents](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- [Number of Positions](#) = 4
- Configuration (Pole-Throw) = Single Pole - Four Throw
- Actuator Style = Extended, Side
- Mount Angle = Vertical
- Grade = Instrumentation
- Termination Type = PC
- PCB Retention Feature = Yes

### Electrical Characteristics:

- Contact Rating = 0.4 VA max @ 20 VDC or peak AC, 300mA @ 125 VAC

### Body Related Features:

- Actuator Color = Black
- Series = MSSA
- Mount Style = Through-Hole
- PCB Tail Length (mm [in]) = 3.51 [0.136]
- PCB Retention Method = Guide Posts
- Actuator Length (mm [in]) = 9.02 [0.355]
- Actuator Material = Polyester
- Flammability Rating = UL 94V-0
- Actuator Travel = 2.50 [0.098]

### Contact Related Features:

- Contact Plating = Silver

### Configuration Related Features:

- Terminal Configuration = Standard
- Number of Actuators = Single

### Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C

### Identification Marking:

- Stamped Marking = With

### Other:

- Brand = Alcoswitch