

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Vss	Vdd	Vo	RS	R/W	Ε	DB0	DB1	DB5	DB3	DB4	DB5	DB6	DB7	EL1	EL2

NOTES:

1.DISPLAY TYPE: STN/BLUE MODE

2.VIEWING DIRECTION: 6:00

3.POLARIZER MODE: TRANSFLECTIVE/NEGATIVE

4.DPERATING TEMP: 0°C--+50°C 5.STORAGE TEMP: -20°C--+60°C 6.LCD OPERATING VOLTAGE: 4.8V

7.DRIVE METHOD: DUTY 1/16 BIAS 1/5 8.CONTROLLER: SPLC780A1-01C-C 9.ALL UNMARKED TOLERANCES: ±0.3mm

10.BACKLIGHT: EL(WHITE)
11.BEZEL IS TO BE PAINTED BLACK

26. 1.15 1.15 1.15 1.15 1.15 1.15



TIAN-MA MICROELECTRONICS CO.

22/F., HANGDU Building, Shennan Road, Central, Shenzhen, China

DRAWN	BY:	TITLI	e TN	1202MFB6			₽
CHECKED	BY:		- ''	1202111 20		SCALE:	7
APPROVED	BY:	DWG	NO:	G-3		UNIT:	mm
CONFIRMED	BY:	DWG	NAME:	TM202MFB6G-3	SHEET	' NO:	OF