

**MICRO SWITCH**  
a Honeywell Division

SWITCH-BASIC

CATALOG LISTING  
WZ-2RQW55-W104

FED. MFG. CODE 91929

CATALOG LISTING  
WZ-2RQW55-W104  
PAGE 1 OF 1

REPLACES X97380-WZ

RELEASE NO. PR-20927

ISSUE  
4

REVISIONS  
A CO-80384  
S A V  
2 MAY 95  
B CO-83108  
G J W  
21 JUN 96  
C C093552  
TSM  
20 JAN 99

CHECK

CHECK

16 FEB 94

16 FEB 94

16 FEB 94

16 FEB 94

16 FEB 94

16 FEB 94

16 FEB 94

16 FEB 94

FORMTEK

DRAWN

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

**CHARACTERISTICS**

OPERATING FORCE — — — — — 2.5 OZ MAX  
PRETRAVEL — — — — — .500 MAX

**ELECTRICAL DATA**

CONTACT ARRANGEMENT  
S P N C

15A-125,250 OR 480 VAC

THIRD ANGLE PROJECTION	
SCALE FULL	
DO NOT SCALE PRINT	
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
ONE PLACE	(.0) ±.030
TWO PLACE	(.00) ±.015
THREE PLACE	(.000) ±.005
ANGLES	±
WEIGHT	

ANSI Y14.5M-1982 APPLIES

**NOTES**

- 1 MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF  $\phi .139$  MAX ON  $1.000 \pm .002$  CENTERS
- 2 - SEALED CONSTRUCTION PROVIDES SPLASH RESISTANCE
- 3 - ACTUATOR LEVER PROVIDES OMNI DIRECTIONAL ACTUATION
- 4 PACKARD-METRIPAK 280 SERIES  
15300027 CONNECTOR  
12010293 SEAL  
12077412 TERMINAL  
15300014 SEC LOCK
- 5 BLACK LEAD IS ATTACHED TO THE COMMON TERMINAL  
WHITE LEAD IS ATTACHED TO THE N.C. TERMINAL

