

Axial Leaded Ceramic Capacitors

TP025F223Z-A-BJ



■ Features

- Item Summary
25V, 0.022 μ F, -20% to 80%, Axial
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping 5000pcs

■ Products characteristics table

| | |
|---------------------------------------|---------------------------|
| External Dimensions (EIA/JIS) | Axial/Axial |
| Rated Voltage (max) | 25V |
| Capacitance | 0.022 μ F |
| Capacitance Tolerance | -20% to 80% |
| Resistance | 1,000 M Ω min. |
| Dielectric Loss Tangent | 7.5%MAX |
| Temperature Characteristics (EIA/JIS) | -/F |
| Temperature Range (EIA/JIS) | -/-25 to +85 $^{\circ}$ C |
| Capacitance Change (EIA/JIS) | -/-80,+30% |
| RoHS Compliance | Yes |
| Soldering Method | Wave |

■ External Dimensions

| | |
|---|-----------|
| L | 2.3mm - |
| D | 2.0mm max |

2015.02.10

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.