


| Specifications        |              |       | Notes   | Revision History       |                           |                   |             |                    |             |
|-----------------------|--------------|-------|---|------------------------|---------------------------|-------------------|-------------|--------------------|-------------|
| Description           | Value        | Unit  |   | Version                | Description               | Date              | Approved    |                    |             |
| Shape                 | Rectangle    |       | 1) All dimensions are in mm unless otherwise noted<br>2) All parts meet RoHS<br><div style="text-align: center;"> <br/> <b>DB UNLIMITED</b> </div> | 1                      | Released from Engineering | 2/5/2014          | J.S.        |                    |             |
| Resonant Frequency    | 220          | (Hz)  |   |                        |                           |                   |             |                    |             |
| Frequency Range       | 220 ~ 20,000 | (Hz)  |   |                        |                           |                   |             |                    |             |
| SPL @ 10cm            | 103          | (dBA) |   |                        |                           |                   |             |                    |             |
| Impedance             | 4            | (Ohm) |   |                        |                           |                   |             |                    |             |
| Cone Material         | Paper        |       |   |                        |                           |                   |             |                    |             |
| Nominal Power         | 5            | (W)   |   |                        |                           |                   |             |                    |             |
| Max Power             | 10           | (W)   |   |                        |                           |                   |             |                    |             |
| Mount Type            | Frame Mount  |       |   |                        |                           |                   |             |                    |             |
| Operating Temperature | -25 ~ +55    | °C    |   |                        |                           |                   |             |                    |             |
| Storage Temperature   | -25 ~ +55    | °C    |   |                        |                           |                   |             |                    |             |
| Weight                | 127          | (g)   |   |                        |                           |                   |             |                    |             |
|                       |              |       |   | <b>Dynamic Speaker</b> |                           | <b>SP900204-1</b> |             |                    |             |
|                       |              |       |   | <b>Drawn by</b>        | <b>Date</b>               | <b>Checked by</b> | <b>Date</b> | <b>Approved by</b> | <b>Date</b> |
|                       |              |       |   | G.W.                   | 1/27/2014                 | C.E.              | 1/29/2014   | J.S.               | 2/5/2014    |