



1201-11-9

REVISIONS	
ISSUE	CHANGES
0	ER 33882 JCA 04/22/92
B	REVISED PER DMF304 & ER34205 KPL 08/05/11

CUSTOMER SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE	4:1		
APPROX SURFACE AREA			
WAS:	E-17428		
CAGE CODE:	91836		
REF:	BOEING		
<h1>JACK, PANEL, N</h1>			
DRAWN	JCA	DATE	04/21/92
DESIGN	JT	DATE	04/22/92
APPR.		DATE	

NOTES:

- FOR USE WITH BOEING BMS13-65 OE & ADAMS RUSSELL FC11Z CABLES.
- FOR CABLING INSTRUCTIONS SEE 3-546-1.
- FOR CRIMPING USE DIE KTH-2214.
- INTERFACE PER MIL-STD-348, FIG. 304-2.
- FOR USE WITH .22 MAX. PANEL.
- CENTER CONTACT M (1-2359-1MA9) SUPPLIED UNASSEMBLED.
- MARK PACKAGE: KINGS 1201-11-9 (DATE CODE)
- MATERIALS:
INSULATOR: TEFLON, ASTM-D1710
K-GRIP SLEEVE: COM. BRONZE TUBE, ASTM B135
CENTER CONTACT F-F: BER. COP., ASTM-B196
ALL OTHER PARTS: BRASS, ASTM-B16

- FINISHES:
CENTER CONTACTS: .000050 MIN GOLD PLATE PER ASTM-B488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290 (RoHS)
ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
- ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS
VOLTAGE RATING: 1000 VRMS
FREQUENCY RANGE: DC TO 11 GHz
- WEIGHT: 48.8 GRAMS

WINCHESTER ELECTRONICS
Winchester Electronics Corporation
62 Barnes Industrial Road North
Wallingford, Connecticut 06492

1201-11-9