


MSP103C Product Details

 [Live Product Chat](#)


Pushbutton Switches

[Not EU RoHS or ELV Compliant \(Find RoHS Compliant Alternates\)](#)

Product Highlights:

- Switch - Mechanical
- Not Tactile
- Single Pole - Single Throw Configuration (Pole-Throw)
- Contact Rating = 3A
- Operating Function = Normally Open, Momentary

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

MSP103C

(8-1437567-4)

TE Internal Number: 8-1437567-4



Superseded

[Search for Replacement Parts](#)

 [Add to My Part List](#)
 [Request Sample](#)
 [Find Similar Products](#)
 [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [ALCOSWITCH PRODUCTS](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Switch - Mechanical
- Tactile = No
- Configuration (Pole-Throw) = Single Pole - Single Throw
- Mount Angle = Vertical
- Termination Type = Wire Lugs
- Actuator Style = Round

Electrical Characteristics:

- Contact Rating = 3A

Body Related Features:

- [Series](#) = MSP3
- Mount Style = Panel
- Actuator Length (mm [in]) = 2.50 [0.098]
- Actuator Profile = Extended
- Actuator Color = Red
- Bushing Diameter = 1/4-40
- Case Material = Thermoplastic (LCP)
- Actuator Material = Thermoplastic

Contact Related Features:

- Contact Plating = Silver
- Contact Base Material = Copper Alloy

Housing Related Features:

- Process Sealed = No
- Low Profile = No
- Bushing Style = Threaded

Configuration Related Features:

- Operating Function = Normally Open, Momentary
- Ganged = No
- ESD Grounding Terminal = Without
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without
- Bushing Length (mm [in]) = 5.94 [0.234]

Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Hand solderable with tin/lead solder

Conditions for Usage:

- Temperature Rating = Standard

Packaging Related Features:

- Packaging Method = Loose Piece

Other:

- Brand = Alcoswitch

[Provide Website Feedback](#) | [Need Help?](#)