THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. PANDU I T DESCRIPTION **WEIGHT** PART NO.* 24 PORT ANGLED 4 PAIR 1.12 LB DPA245E88TV25 CATSE RJ21 PATCH PANEL (507g) 3.93 NOTES: [99.7] * 1. SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS WITH THIS WIRING SYSTEM AS WELL AS OPTIONAL SNAP-IN LABEL HOLDERS. 2. 24 PORT ANGLED PATCH PANEL ALL PAIR WIRED 8 POSITION RJ45 MODULE ALL — 19.00 [482.6] — POSITIONS WIRED. 3. THE PATCH PANEL IS DESIGNED FOR MOUNTING TO 19" UNIVERSAL RACKS. 18.32 [465.3] TYP. -4. FOUR (4) 12-24 X 1/2" ROUND HEAD SCREWS AND (4) METRIC M6×1×15MM 1.72 DPLK24 LABEL KIT LOCATES HERE SCREWS ARE PROVIDED FOR FASTENING 43.6 IDENTIFIES PATCH PANEL. TO RACKS. OPTIONAL. NOT SUPPLIED. 5. DIMENSIONS IN PARENTHESES ARE IN METRIC. .28 -6. MATERIALS - STAMPING: CRS HOOK AND LOOP STRAP [7.1] MODULE: V-O ABS (4 PLACES) /B\ MOUNTS TO 19" UNIVERSAL RACKS DPLK24 LABEL KIT LOCATES HERE [10.2] MODEL FILENAME IDENTIFIES INDIVIDUAL PORTS. SIZE M02829AB_4PAIR_5E_24PORT_ANGLED_00 (4 PLACES) OPTIONAL. NOT SUPPLIED. DRAWING FILENAME M02829AB_DC12_00B.PRT 24 PORT ANGLED 4 PAIR CAT 5e RJ21 PATCH PANEL CUSTOMER DRAWING I.I. NUMBER CORP PRODUCT SPEC TINLEY PARK, ILL 60477 WORK INSTRUCTION ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: SCALE (.X) ±.03 (.XXX) ±.005 NONE THIRD ANGLE (.XX) ±.01 ANGLES ± 1° PART NO. DRAWN BY REVIEW DRAWING NUMBERS B. ADDED (4 PLACES). 02829-12 MKY 10-31-07 MDJr MKY RDE MKY A. LABEL PART# WAS DPLT. NER DPA245E88TV25 DATE 8-17-07 RELEASED TO PRODUCTION NER CEF 02829-12 CEF CEF CEF 8-17-07 02829 - 12 DATE DESCRIPTION R CUST SUP ОТН BY CHK ECN -MKY SHEET 1 OF 2