

Type:

BCR100

Dedicated, remote driver LED fixture designed for closet rod applications



- Extruded aluminum housing available in anodized polished chrome, satin aluminum, polished brass, and antique bronze finish (consult factory for custom finishes)
 - Available in sizes from 12" to 96"
 - All fixtures made to specified length $\pm 1/16"$
 - Includes frosted or clear acrylic lens
 - Fitting secures to surface with supplied mounting hardware and optional center support bracket which match body finish
 - Center support bracket required for installations over 36"
 - 33 lb. capacity up to 3' length
 - LED CRI Typ 85
 - 9 watts per linear foot
 - Limited 3 year warranty
- DRIVER:
- UL recognized class 2
 - Constant current
 - Life: 50,000 hrs
 - Input voltage: 120-277V
 - Output voltage: 55V max
- Remote aluminum enclosure 13" L x 2-11/16" W x 1-7/8" H

LENGTH

COLOR TEMPERATURE

LENS

FINISH

BCR100

+

—
please specify to the nearest 1/16" (from 12" to 96")

+

—
27: 2700K
30: 3000K
35: 3500K
40: 4000K
50: 5000K


+

—
C: clear
F: frosted


+

—
CH: polished chrome
SA: satin aluminum
BR: polished brass
AB: antique bronze
CF: consult factory for custom color


Profile



Plan



Photometric



Maximum Candela = 1340.9 Located At Horizontal Angle = 0, Vertical Angle = 5
1 - Vertical Plane Through Horizontal Angle = 0, Vertical Angle = 5
2 - Horizontal Cone Through Vertical Angle (5) (Through Max. Cd.)