

-			1		2 3
			STANDAR	D APPLICATION	ON.
	PIN	NUMBER OF	SOLDER TAIL	LEFT	RIGHT
	STYLE		REF	POLARIZATION	
	30	2 x 2	3.05	NO NO	NO
	31	2 x 3	3.05	NO NO	NO
	32 01	2 x 4 2 x 5	3.05 3.05	NO NO	NO YES
	02	2 x 3	3.05	NO NO	YES
A	03	2 x 7	3.05	YES	YES
~	04	2 x 10	3.05	YES	YES
	05	2 x 13	3.05	YES	YES
	33	2 x 15	3.05	YES	YES
	06	2 x 17	3.05	YES	YES
	07	2 x 20	3.05	YES	YES
	08	2 x 25	3.05	YES	YES
	09	2 x 30	3.05	YES	YES
	10	2 x 32	3.05	YES	YES
В	PLA	TING :			
Junect.com	1	= 0.76µm			
FCIconnect			TH GOLD FL N MATTE TIN		NTACT AREA
\bigcirc	2	= 2µm TIN	N MIN FULL	PLATED	
	3	= 0.38µm	GOLD/GXT		
				ASH) ON CO	NTACT AREA
<u>c</u>			MATTE TIN		
무		LINDERDI	_ATE : 1.27μ	ım Ni MIN	
Copyright FCI		UNDLINI	_ATL . 1.27,L	ATTI INI IVIIIN	
pyrig					
ا ق					
`_`					
n					
.	form: A3		1		2
				I	

