

GPS Triple Series

195 WATT LINEAR

FEATURES

- 3 Independent Isolated Output
- Four "3 Digits" LED Display
- 0.01% Load and Line Regulation
- Low Ripple and Noise
- Tracking Operation and Auto Series/Parallel Operation
- Output ON/OFF Switch
- Output Voltage and Current Setting When Output Disable
- Fan Speed Control Circuit to Minimize Fan Noise
- Over Load and Reverse Polarity Protection



SPECIFICATIONS

CONSTANT VOLTAGE OPERATION (CH1, CH2)

Line regulation	$\leq 0.01\% + 3mV$
Load regulation	$\leq 0.01\% + 3mV$ (rating current $\leq 3A$) $\leq 0.02\% + 5mV$ (rating current $> 3A$)

Ripple & noise	$\leq 1mV_{rms}$ 5Hz ~ 1MHz
----------------	-----------------------------

Recovery tTime	$\leq 100mS$ (50% load change, minimum load 0.5A)
----------------	---

CONSTANT CURRENT OPERATION (CH1, CH2)

Line regulation	$\leq 0.2\% + 3mA$
Load regulation	$\leq 0.2\% + 3mA$

Ripple current	$\leq 1mV_{rms}$ 5Hz ~ 1MHz
----------------	-----------------------------

5V FIXED OUTPUT

Regulation	Line regulation $\leq 5mV$ Load regulation $\leq 10mV$
Ripple & noise	$\leq 3mArms$

TRACKING OPERATION (CH1, CH2)

Tracking error	$\leq 0.5\% + 10mV$ of CH1
Series regulation	$\leq 0.01\% + 5mV$

Load regulation	$\leq 300mV$
-----------------	--------------

Ripple & noise	$\leq 2mV_{rms}$, 5Hz ~ 1MHz
----------------	-------------------------------

FIXED OUTPUT (CH3)

Voltage	5V
Line regulation	$\leq 5mV$

Load regulation	$\leq 10mV$
-----------------	-------------

Ripple & noise	$\leq 2mV_{rms}$
----------------	------------------

Output current	3A
----------------	----

METER

Digital	3 1/2 digits 0.5" LED display
Accuracy	$\pm(0.5\% \text{ of rdg} + 2 \text{ digits})$

SAFETY

IEC/EN 61010-1

CE mark	Yes
---------	-----

INSULATION

Chassis and terminal	$\leq DC 500V / 20MW$
Chassis and AC cord	$\leq DC 500V / 30MW$

POWER SOURCE

Input voltage	AC 100V/120V/220V $\pm 10\%$, 230V(+10% ~ - 6%), 50/60Hz
---------------	---

DIMENSIONS & WEIGHT

Case	255(W) x 145(H) x 265(D) mm Approx 7kg
------	---

SELECTION TABLE

MODEL NUMBER	CH1 / CH2	CH3	TRACKING SERIES V	TRACKING PARALLEL I
GPS-3303	0-30V / 0-3A	5V / 3A Max	60V / 3A	30V / 6A