


ICO300

Robust Din-rail Fanless Embedded System with Intel® Atom™ Processor E3815/E3827
4 COM, 2 LANs, DIO and RTC



▲ Front view




Features

- Fanless design
- Supports Intel® Atom™ processor E3815 (1.46GHz) or E3827 (1.75GHz)
- 4 RS-232/422/485 COM ports
- Supports Windows® 10 IoT Solution
- 2 isolated 10/100/1000Mbps Ethernet ports
- 1 DIO port
- 1 wireless (3G/GPRS or Wi-Fi)
- Supports 1 CompactFlash™ (or mSATA) and SATA SSD (or HDD)
- Wide range 12 - 24V DC-In




▲ Rear view



VGA

▲ ICO300



DIO

▲ ICO300-DIO

Specifications

Standard Color	White
Construction	Extruded aluminum and heavy-duty steel, IP40
CPU	Intel® Atom™ Processor E3815 (1.46GHz) or E3827 (1.75GHz)
System Board	SBC87842
System Memory	DDR3L-1066 MHz SO-DIMM up to 4 GB (E3815), up to 8 GB (E3827)
BIOS	AMI UEFI BIOS
System I/O Outlet	Serial Port 4 x RS-232/422/485 (COM 1-4) Interface select by BIOS Supports Auto Flow Control in RS-485 mode
	USB 2 x USB 2.0
	RTC Battery onboard
Storage	Supports 1 x CF* (or mSATA*) Supports 1 x SATA SSD (or HDD)
LAN	2 x 10/100/1000 Ethernet
VGA	1 x DB15 connector
DIO (ICO300-DIO)	1 x DI/DO (8 bit programmable, DB9 female connector) Voltage is 5V TTL-level ESD protection corresponds to IEC6100-4-2 (± 8KV (Air); ± 4KV (contact)) Programming: I/O sink current is 10mA (max.) Input/output can be programming
Power Input	1 x DC power input with terminal block
Wireless	1 x full size Mini Card slot Supports wireless* (3G/GPRS or Wi-Fi) 1 x SIM socket 2 x Antenna

Watchdog Timer	255 levels, 1-255 sec
System Indicator	Power, Active
Power Supply	Power Input Range : 12-24VDC Power Input Rating : 12-24VDC, 1.21-0.66A Power Protection : DC Version, OVP, Reverse protection
Operating Temperature	-20°C ~ +70°C (-4°F ~ +158°F)
Storage Temperature	-40°C ~ +85°C (-40°F ~ +185°F)
Humidity	10% ~ 95%
Vibration Endurance	2g@5-500Hz, amplitude 0.35 mm (operation/storage/transport)
Weight (net/gross)	1.0 kg (2.2 lb)/1.50 kg (3.3 lb)
Certificate	CE, FCC
Dimensions	48 mm (1.88") (W) x 110 mm (4.33") (D) x 155 mm (6.1") (H)
EOS Support	Windows® 7 Embedded Windows® 8 Embedded Linux support package Windows® 10 IoT

* mSATA and wireless can be either one.

* mSATA and CF can be either one.

Ordering Information

Standard

IC0300-E3815-DC	Robust din-rail fanless embedded system with Intel® Atom™ Processor E3815 1.46 GHz and 4 COM ports (-20°C ~ +70°C)
IC0300-E3827-DC	Robust din-rail fanless embedded system with Intel® Atom™ Processor E3827 1.75 GHz and 4 COM ports (-20°C ~ +70°C)
IC0300-E3815-DIO-DC	Robust din-rail fanless embedded system with Intel® Atom™ Processor E3815 1.46 GHz, 4 COM ports and DIO (-20°C ~ +70°C)
IC0300-E3827-DIO-DC	Robust din-rail fanless embedded system with Intel® Atom™ processor E3827 1.75GHz, 4 COM ports and DIO (-20°C ~ +70°C)

Optional

CompactFlash™	4 GB or above (with W.T. CF)
2.5" SATA SSD or HDD (with W.T. SSD or HDD)	
DDR3L SODIMM	2 GB ~ 8 GB (with W.T. memory)
Wall Mounting Kit	
Wireless (3G/GPRS or Wi-Fi) module	

*Specifications and certifications are based on options and may vary.

Dimensions

