



1	2	3	4	5	6	7	8	9
VSS	VDD	V0	D/Ī	R/W	E	DB0	DB1	DB2
10	11	12	13	14	15	16	17	18
DB3	DB4	DB5	DB6	DB7	CS1	CS2	RST	Vout

- NOTES:
- 1.DISPLAY TYPE: STN/YELLOW MODE
  - 2.VIEWING DIRECTION: 6:00
  - 3.POLARIZER MODE: TRANSFLECTIVE/POSITIVE
  - 4.OPERATING TEMP: -10°C~+60°C
  - 5.STORAGE TEMP: -30°C~+70°C
  - 6.DRIVE METHOD: 1/64 DUTY 1/9 BIAS
  - 7.BACKLIGHT TYPE: LED
  - 8.CONTRROLLER: KS0108B
  - 9.LCD OPERATING VOLTAGE: 13.0V
  - 10.BEZEL IS TO BE PAINTED BLACK
  - 11.UNMARKED TOLERANCES: ±0.3mm

 <b>TIAN-MA MICROELECTRONICS CO.</b> 22/F., HANGDU Building, Shennan Road, Central, Shenzhen, China		
DRAWN BY: _____ CHECKED BY: _____ APPROVED BY: _____ CONFIRMED BY: _____	TITLE: M12864BBCW6 DWG NO: G-1 DWG NAME: TM12864BBCW6G-1	
		SCALE: _____ UNIT: mm SHEET NO: 0F