

**Micro Commercial Components** 



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

### **Features**

- High Reliability
- Low Reverse Current and Low Forward Voltage
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates Compliant. See ordering information)
- Moisture Sensitivity Level 1

### **Maximum Ratings**

- Operating Temperature: -65°C to +125°C
- Storage Temperature: -65°C to +150°C


### Electrical Characteristics @ 25°C Unless Otherwise Specified


Parameter	Symbol	Test	Condition	
Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	40V	IR = 10 μ A	
Average Forward Current	I <sub>F(AV)</sub>	0.35A	T <sub>a</sub> = 25℃	
Peak Forward Surge Current	I <sub>FSM</sub>	7.5A	$t_p \leq 10ms$	
Junction Ambient	$R_{thJA}$	300K/W	On PC board 50mm $\times$ 50mm $\times$ 1.6mm	

Note:1.Lead in Glass Exemption Applied, see EU Directive Annex 7(C)-I.

# 350mA Schottky Barrier Rectifier 40 Volts

**BAS48** 





www.mccsemi.com

**Revision:** B

**20**12/**0**1/**0**1



### Electrical Characteristics @ 25°C Unless Otherwise Specified

Parameter	Test Conditions	Symbol	Min	Тур	Max	Unit
Forward voltage	I <sub>F</sub> =1mA	VF			0.3	V
	I <sub>F</sub> =10mA	V <sub>F</sub>			0.4	V
	I <sub>F</sub> =200mA	VF			0.75	V
Reverse current	V <sub>R</sub> =40V	IR			25	$\mu A$
Junction capacitance	V <sub>R</sub> =1V, f=1MHz	CJ		12		pF

# www.mccsemi.com

**Revision:** B

### BAS48






Figure 1. Admissible power dissipation vs. ambient temperature




Figure 2. Forward characteristics




Figure 3. Typical reverse characteristics

## www.mccsemi.com

**Revision:** B



### **Ordering Information :**

Device	Packing		
Part Number-TP	Tape&Reel: 2.5Kpcs/Reel		

#### **\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

## www.mccsemi.com

**Revision:** B