



Advanced Product Information
May 1996 (1 of 2)

Features

- ☐ High Gain
- ☐ +36 dBm Power Output
- ☐ Proprietary Power FET Process
- ☐ >45% Linear Power Added Efficiency
- ☐ +33 dBm with 30 dBc Third Order Products

Applications


- ☐ ISM Band Base Stations
- ☐ Cellular Base Stations
- ☐ Wireless Local Loop

Description

The CFH2162-P1 is a high-gain, linear FET intended for driver amplifier applications in high-power systems, and output stage usage in medium power applications at power levels up to +36 dBm. The device is easily matched and pro-

800 to 900 MHz +36 dBm Power GaAs FET

Package Diagram



vides excellent linearity at 4 Watts. Manufactured in Celeritek's proprietary power FET process, this device is assembled in a power flange package.

Specifications (TA = 25°C) The following specifications are guaranteed at room temperature in Celeritek test fixture at 850 MHz.

Parameters	Conditions	Min	Typ	Max	Units
V_d = 10V, I_d = 1100 mA (Quiescent)					
P-1dB		36.0	37.0	—	dBm
G-1 dB		19.0	20.0	—	dB
3rd Order Products ⁽¹⁾		30	35	—	dBc
Efficiency	@ P1dB	—	45	—	%
V_d = 8V, I_d = 1300 mA (Quiescent)					
P-1dB		—	36.0	—	dBm
G-1 dB		—	19.0	—	dB

Parameters	Conditions	Min	Typ	Max	Units
g _m	V _{ds} = 2.0V, V _{gs} = 0V	—	1700	—	mS
I _{dss}	V _{ds} = 2.0V, V _{gs} = 0V	—	2.8	—	A
V _p	V _{ds} = 3.0V, I _{ds} = 65 mA	—	-1.8	—	Volts
BV _{GD}	I _{gd} = 6.5 mA	20	24	—	Volts
Θ _{JL} (2)	@150°C TCH	—	8	—	°C/W


Absolute Maximum Ratings

Parameter	Symbol	Rating
Drain-Source Voltage	V _{DS}	15V ⁽³⁾
Gate-Source Voltage	V _{GS}	-5V
Drain Current	I _{DS}	I _{dss}
Continuous Dissipation	P _T	10W
Channel Temperature	T _{CH}	175°C
Storage Temperature	T _{STG}	-65°C to +175°C

Notes:

- Sum to two tones with 1 MHz spacing = 33 dBm.
- See thermal considerations information.
- Maximum potential difference across the device (V_d + V_g) cannot exceed 18V.

Power Flange Package Physical Dimensions



Ordering Information

The CFH2162-P1 power stage is available in a SOIC-8 surface mount package. Devices are available in tape and reel. Ordering part numbers are listed.

<u>Part Number for Ordering</u>	<u>Function</u>	<u>Package</u>
CFH2162-P1	800 - 900 MHz Power Stage	Power flange package

Celeritek reserves the right to make changes without further notice to any products herein. Celeritek makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Celeritek assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters can and do vary in different applications. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Celeritek does not convey any license under its patent rights nor the rights of others. Celeritek products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Celeritek product could create a situation where personal injury or death may occur. Should Buyer purchase or use Celeritek products for any such unintended or unauthorized application, Buyer shall indemnify and hold Celeritek and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Celeritek was negligent regarding the design or manufacture of the part. Celeritek is a registered trademark of Celeritek, Inc. Celeritek, Inc. is an Equal Opportunity/Affirmative Action Employer.