



1. Mechanical Dimensions:



2. Schematic:



3. Electrical Specifications:

Inductance: 470uH±15% @1KHz, 1.0V

Inductance: 293.8uH±15% @1.6Adc

DC Resistance: 0.28 Ohms Max

Q: 20 Min @10KHz, 0.1V

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -55°C to +105°C
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. Electrical and mechanical specifications 100% tested
9. RoHS Compliant Component

DOC. REV. A/1

XFMRS Inc. www.XFMRS.com	Title: Toroid Inductor		
	UNLESS OTHERWISE SPECIFIED TOLERANCES: .xxx ±0.010 Dimensions in Inch		P/N: 1XF4706-VP
SHEET 1 OF 1	DWN.	Mei Chen	Sep-22-10
	CHK.	YK Liao	Sep-22-10
	APP.	BW	Sep-22-10

PROPRIETARY

Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.