

## 82842 Multi-Conductor - Low Capacitance Computer and Computer P.O.S. Cable



For more Information  
please call

1-800-Belden1



### General Description:

Low cap 24 AWG stranded (7x32) TC conductors, plenum, foam FEP insulation, twisted pairs, overall Beldfoil (100% coverage) + TC braid shield (90% coverage), 24 AWG stranded TC drain wire, Flam arrest® jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Pairs	AWG	Stranding	Conductor Material
2	24	7x32	TC - Tinned Copper

Total Number of Conductors: 4

#### Insulation

##### Insulation Material:

Insulation Trade Name	Insulation Material	Wall Thickness (mm)
Teflon®	FFEP - Foam Fluorinated Ethylene Propylene	0.483

#### Outer Shield

##### Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	90

##### Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
22	7x32	TC - Tinned Copper

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material	Nom. Wall Thickness (mm)
Flam arrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.381

#### Overall Cable

Overall Nominal Diameter: 6.934 mm

#### Pair

##### Pair Color Code Chart:

Number	Color
1	White/Blue & Blue/White
2	White/Orange & Orange/White

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

Bulk Cable Weight: 56.552 Kg/Km

Max. Recommended Pulling Tension: 252.213 N

Min. Bend Radius/Minor Axis: 69.850 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

METRIC MEASUREMENT VERSION

## 82842 Multi-Conductor - Low Capacitance Computer and Computer P.O.S. Cable

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

## Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	9842

## Electrical Characteristics (Overall)

## Nom. Characteristic Impedance:

Impedance (Ohm)

120

## Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

39.372

## Nom. Capacitance Cond. to Other Conductor &amp; Shield:

Capacitance (pF/m)

72.182

## Nominal Velocity of Propagation:

VP (%)

76

## Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

78.744

## Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

7.8744

## Max. Operating Voltage - UL:

Voltage

300 V RMS

## Max. Recommended Current:

Current

3.2 Amps per conductor @ 25°C

## Notes (Overall)

Notes: Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

## METRIC MEASUREMENT VERSION

### 82842 Multi-Conductor - Low Capacitance Computer and Computer P.O.S. Cable

82842 8771000	305 MT	19.051 KG	NATURAL	C	2 PR #24 FFEP SH FLRST
82842 877500	152 MT	9.525 KG	NATURAL	C	2 PR #24 FFEP SH FLRST
82842 8775000	1,524 MT	95.255 KG	NATURAL		2 PR #24 FFEP SH FLRST

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 08-15-2012

© 2013 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.