



Electro-Static Discharge TESD05CB Bidirectional TVS Diode

DFN1006



Pin Configuration



Features

- 100 Watts Peak Pulse Power per Line ($t_p=8/20\mu s$)
- Protects one bidirectional I/O line
- Low clamping voltage
- Working voltages : 5V
- Low leakage current

IEC Compatibility

- IEC61000-4-2 (ESD) $\pm 25kV$ (air), $\pm 25kV$ (contact)
- IEC61000-4-4 (EFT) 40A (5/50 ηs)

Applications

- Cell Phone Handsets and Accessories
- Microprocessor based equipment
- Personal Digital Assistants (PDA's)
- Notebooks, Desktops, and Servers
- Portable Instrumentation
- Peripherals
- Pagers

Mechanical Characteristics

- JEDEC DFN1006 Package
- Molding Compound Flammability Rating : UL 94V-O
- Weight 0.5 Milligrams (Approximate)
- Quantity Per Reel : 10,000pcs
- Reel Size : 7 inch
- Lead Finish : Lead Free

Maximum Ratings($T_A=25^\circ\text{C}$ unless otherwise specified)

| Parameter | Symbol | Value | Units |
|--|-----------|--------------|-------|
| Peak Pulse Power($tp=8/20\mu\text{s}$) | P_{PP} | 100 | Watts |
| Lead Soldering Temperature | T_L | 260(10 sec.) | °C |
| Operating Temperature Range | T_J | -55~150 | °C |
| Storage Temperature Range | T_{STG} | -55~150 | °C |

Electrical Characteristics($T_A=25^\circ\text{C}$ unless otherwise specified)

TESD05CB(Marking: .H)

| Parameter | Symbol | Conditions | Min. | Typ. | Max. | Units |
|---------------------------|-----------|--|------|------|------|-------|
| Reverse Stand-off Voltage | V_{RWM} | | | | 5 | V |
| Breakdown Voltage | V_{BR} | $I_T=1\text{mA}$ | 5.6 | | | V |
| Clamping Voltage | V_C | $I_{PP}=1\text{A}, tp=8/20\mu\text{s}$ | | | 9.5 | V |
| | | $I_{PP}=4\text{A}, tp=8/20\mu\text{s}$ | | | 15 | V |
| Reverse Leakage Current | I_R | @ V_{RWM} | | | 1 | μA |
| Junction Capacitance | $C_{I/O}$ | 0Vdc, f=1MHz Between I/O Pins and GND | | 10 | | pF |

Ratings and Characteristic Curves

Fig.1 Non-Repetitive Pulse Power vs.Pulse Time






Fig.2 Pulse Waveform




Application

Power Protection



Dimensions(DFN1006)

DFN1006



| DIM | Millimeters | | Inches | |
|-----|-------------|------|----------|-------|
| | Min | Max | Min | Max |
| A | 0.95 | 1.07 | 0.037 | 0.042 |
| B | 0.55 | 0.65 | 0.022 | 0.026 |
| C | 0.45 | 0.55 | 0.017 | 0.022 |
| D | 0.20 | 0.30 | 0.008 | 0.012 |
| E | 0.65BSC | | 0.026BSC | |
| F | 0.40 | 0.55 | 0.015 | 0.022 |
| G | 0.00 | 0.10 | 0.000 | 0.004 |

Recommended Mounting Pad Layout

