



# Multilayer Balun

For 1710-1880MHz

# HHM1731F1

---

**1.6x0.8mm [EIA 0603]\***

\* Dimensions Code JIS[EIA]

# Multilayer Balun


For 1710-1880MHz

Conformity to RoHS Directive


## HHM1731F1

### SHAPES AND DIMENSIONS

[Top view]



[Bottom view]




#### Terminal functions

|   |                        |
|---|------------------------|
| 1 | Unbalanced port        |
| 2 | GND or DC feed+ RF GND |
| 3 | Balanced port          |
| 4 | Balanced port          |
| 5 | GND                    |
| 6 | N.C.                   |

Dimensions in mm

### RECOMMENDED LAND PATTERN



○ RoHS Directive Compliant Product: See the following for more details related to RoHS Directive compliant products. <http://product.tdk.com/en/environment/rohs/>

- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

## HHM1731F1

## ■ ELECTRICAL CHARACTERISTICS

| Item                                                  | Frequency Range (MHz) | Min. | Typ.          | Max. |
|-------------------------------------------------------|-----------------------|------|---------------|------|
| Unbalanced Port Characteristic Impedance ( $\Omega$ ) |                       |      | 50 (Nominal)  |      |
| Balanced Port Characteristic Impedance ( $\Omega$ )   |                       |      | 200 (Nominal) |      |
| Return Loss at Unbalanced Port (dB)                   | 1710 to 1880          | 10   | —             | —    |
| Phase Balance (deg.)                                  | 1710 to 1880          | 170  | —             | 190  |
| Amplitude Balance (dB)                                | 1710 to 1880          | −1.5 | —             | 1.5  |
| Insertion Loss (dB)                                   | 1710 to 1880          | —    | —             | 1.2  |

## ■ TEMPERATURE RANGE


| Operating temperature (°C) | Storage temperature (°C) |
|----------------------------|--------------------------|
| −40 to +85                 | −40 to +85               |

- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.


## HHM1731F1

## FREQUENCY CHARACTERISTICS


## INSERTION LOSS




## AMPLITUDE BALANCE



## RETURN LOSS




## PHASE BALANCE



- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

## ■ RECOMMENDED REFLOW PROFILE



- 20150419 / rf\_balun\_hhm1731f1

## REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

### SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using these products.

#### REMINDERS

The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.

The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.

Please understand that we are not responsible for any damage or liability caused by use of the products in any of the applications below or for any other use exceeding the range or conditions set forth in this catalog.

- |                                                                   |                                                                              |
|-------------------------------------------------------------------|------------------------------------------------------------------------------|
| (1) Aerospace/Aviation equipment                                  | (8) Public information-processing equipment                                  |
| (2) Transportation equipment (cars, electric trains, ships, etc.) | (9) Military equipment                                                       |
| (3) Medical equipment                                             | (10) Electric heating apparatus, burning equipment                           |
| (4) Power-generation control equipment                            | (11) Disaster prevention/crime prevention equipment                          |
| (5) Atomic energy-related equipment                               | (12) Safety equipment                                                        |
| (6) Seabed equipment                                              | (13) Other applications that are not considered general-purpose applications |
| (7) Transportation control equipment                              |                                                                              |

When using this product in general-purpose applications, you are kindly requested to take into consideration securing protection circuit/equipment or providing backup circuits, etc., to ensure higher safety.