

isc Silicon NPN Power Transistor

2SD254

DESCRIPTION



- Collector-Emitter Breakdown Voltage-
: $V_{(BR)CEO} = 70V(\text{Min})$
- Collector Power Dissipation-
: $P_C = 20W @ T_C = 25^\circ C$
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Designed for use in general purpose amplifier and switching applications.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ C$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	70	V
V_{CEO}	Collector-Emitter Voltage	70	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current-Continuous	3.0	A
I_{CM}	Collector Current-Peak	5.0	A
I_B	Base Current	1.0	A
P_C	Collector Power Dissipation@ $T_C=25^\circ C$	20	W
T_J	Junction Temperature	150	$^\circ C$
T_{stg}	Storage Temperature	-65~150	$^\circ C$



isc Silicon NPN Power Transistor**2SD254****ELECTRICAL CHARACTERISTICS** $T_C=25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{CEQ(SUS)}$	Collector-Emitter Sustaining Voltage	$I_C=30\text{mA}; I_B=0$	70		V
$V_{CE(sat)-1}$	Collector-Emitter Saturation Voltage	$I_C=0.5\text{A}; I_B=50\text{mA}$		1.0	V
$V_{CE(sat)-2}$	Collector-Emitter Saturation Voltage	$I_C=2\text{A}; I_B=1\text{A}$		2.0	V
$V_{BE(on)}$	Base-Emitter On Voltage	$I_C=2\text{A}; V_{CE}=4\text{V}$		1.8	V
I_{CBO}	Collector Cutoff Current	$V_{CB}=70\text{V}; V_{EB}=0$		0.1	mA
I_{CEO}	Collector Cutoff Current	$V_{CE}=70\text{V}; I_B=0$		0.3	mA
I_{EBO}	Emitter Cutoff Current	$V_{EB}=5\text{V}; I_C=0$		0.1	mA
h_{FE-1}	DC Current Gain	$I_C=0.5\text{A}; V_{CE}=2\text{V}$	30	200	
h_{FE-2}	DC Current Gain	$I_C=2\text{A}; V_{CE}=2\text{V}$	15		
f_T	Current-Gain—Bandwidth Product	$I_C=0.5\text{A}; V_{CE}=10\text{V}$	10		MHz