




NOTICE OF PROPRIETARY RIGHTS

THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA, INCLUDING TRADE SECRETS, PROPRIETARY TO TIMES MICROWAVE SYSTEMS. DISCLOSURE OF THIS DATA IS EXPRESSLY CONDITIONED UPON YOUR ASSENT THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY. ANY OTHER USE IS STRICTLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF TIMES MICROWAVE SYSTEMS.

SYM	REVISION DESCRIPTION	DFTM	DATE	APPD	DATE
A	RELEASED FOR PRODUCTION	MS	08/20/03	MS	08/20/03



3-D VIEW

NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.
2. MATERIAL: SHRINK SLEEVE - SHRINKABLE POLYOLEFIN PER MIL-I-23053/5
CONTACT - PHOSPHOR BRONZE PER QQ-B-750
INSULATOR - TEFLON PER ASTM D1710
GASKET - SILICONE RUBBER PER ZZ-R-765
CRIMP SLEEVE - D.H.P. COPPER CDA ALLOY 122
ALL OTHER PARTS - BRASS PER ASTM B16
3. FINISHES: CRIMP SLEEVE - SULFAMATE NICKEL PLATE PER MIL-P-27418
CONTACT - GOLD PLATE PER MIL-G-45204
ALL OTHER METAL PARTS - NICKEL PLATE PER QQ-N-290

DRAFTSMAN	M.SOLAK	08/20/03	TIMES MICROWAVE SYSTEMS 358 HALL AVENUE PO BOX 5039 WALLINGFORD CT 06492-5039		
CHECKER					
APPROVED					
UNLESS OTHERWISE SPECIFIED			TITLE SMA MALE CRIMP		
			DESC. SMA MALE 90° EZ CRIMP FOR LMR-240 CABLE		
TOLERANCES ON DECIMALS .XX ± ANGLES ±		XXX ± FRACTIONS ±	CODE IDENT. 68999	DRVG. NO. 3190-1536	REV. A
DO NOT SCALE DRAWING			SCALE NONE	SHEET 1 of 1	