

# Power Supplies - PS/2 Type

## PS302-XP2

Model Name	P/N : 50903724010E						
PS302-XP2 PS/2 Type ATX 300W	Input Range	100-240Vac Full Range					
	Output Voltage	+5V	+12V1	+12V2	-12V	+5Vsb	+3.3A
		16A	17A	17A	0.3A	2.5A	19A
	MTBF (hours)	AT 25°C 100,000h					
	Safety	UL, CSA, CE, FCC					
	Dimensions	150 x 140 x 86 mm					
Compatible with Axiomtek Products	AX61221, AX61222, AX61220, AX61400, AX6156LE, AX60552, AX60501, AX60551, AX61492						



## PS400-XP2

Model Name	P/N: 50904B24000E						
PS400-XP2 PS/2 Type ATX 400W	Input Range	90 - 264Vac Full Range					
	Output Voltage	+5V	+3.3V	+12V1	+12V2	-12V	+5Vsb
		20A (0.5A min)	20A (0.3A min)	16A (1A min)	16A (1A min)	0.5A	2.5A (1A min)
	MTBF (hours)	AT 25°C 100,000h					
	Safety	TUV, CSA22.2 NO.60950-1, IEC, UL, NEMKO+CB,CE					
	Dimensions	150 x 140 x 74 mm					
Compatible with Axiomtek Products	AX61221, AX61222, AX60501, AX60551, AX60552, AX61400, AX6145, AX6156, AX61492, AX61220						



## PS500-XP2

Model Name	P/N: 50904C06000E							
PS500-XP2 PS/2 Type ATX 500W	Input Range	90 - 265VAC Full Range						
	Output Voltage	+5V	+3.3V	+12V	+12V1	+12V2	-12V	+5Vsb
		24A (0.3A min)	24A (0.5A min)	34A (1A min)	17A (1A min)	17A (1A min)	0.8A	2.5A
	MTBF (hours)	AT 25°C 100,000h						
	Safety	TUV, CUL, CB, IEC60950-1, GB4943-2001, UL60950-1, EN60950-1						
	Dimensions	150 x 140 x 86 mm						
Compatible with Axiomtek Products	AX61221, AX61222, AX60501, AX60551, AX60552, AX61400, AX6145, AX6156, AX61492, AX61220							

