


XLT2404


Single-Stage Thermoelectric Cooler
RoHS EU Compliant



TYPICAL PERFORMANCE VALUES

Hot Side Temperature (°C)	50°C	100°C
ΔT_{max} (°C-dry N ₂):	70	85
Q _{max} (watts):	50	57
I _{max} (amps):	15.2	14.5
V _{max} (vdc):	5.1	6.1
AC Resistance @ 27°C (ohms):	0.25	---

MECHANICAL CHARACTERISTICS




ORDERING OPTIONS

Model Number	Description
XLT2404-04AC	Leadwires, Lapped

PRODUCT FEATURES

- Rated operating temperature 125°C.
- Designed for temperature cycling applications.
- Capable of rapid heating and cooling rates.
- Porch configuration for enhanced leadwire strength.
- Lapped module allows for multiple module applications.

ENVIRONMENT: ONE ATMOSPHERE DRY NITROGEN



For performance information in a vacuum or with hot side temperatures other than 50°C or 100°C, contact one of our Applications Engineers at 877-627-5691.

Installation

Recommended mounting methods: Clamp with uniform pressure to a flat surface with thermal interface material. For additional information, please refer to our TEC Installation Guide.

Operation Cautions

For maximum reliability, storage and operation below 125°C in a non-condensing environment is recommended. To minimize thermal stress, use linear/proportional temperature control or a similar method rather than an ON/OFF method.

CONTACT US:

For customer support or general questions please contact a local office below or visit our website at www.marlow.com.

Marlow Industries, Inc.
 10451 Vista Park Road
 Dallas Texas 75238-1645
 214-340-4900 (tel)
 214-341-5212 (fax)
 877-627-5691 (tech support)
www.marlow.com

Marlow Industries Europe GmbH
 Brunnenweg 19-21
 64331 Weiterstadt
 Germany
 Tel.: +49 (0) 6150 5439 - 403
 Fax: +49 (0) 6150 5439 - 400
 info@marlow-europe.eu

II-VI Japan Inc.
 WBG Marive East 17F
 2-6 Nakase, Mihama-ku
 Chiba-Shi, Chiba 261-7117
 Japan
 81 43 297 2693 (tel)
 81 43 297 3003 (fax)
 center@ii-vi.co.jp
 www.ii-vi.co.jp

II-VI Singapore Pte., Ltd.
 Blk. 5012, Techplace II
 #04-07 & 05-07/12, Ang Mo Kio Ave. 5
 Singapore 569876
 (65) 6481 8215 (tel)
 (65) 6481 8702 (fax)
 info@ii-vi.com.sg
 www.ii-vi.com.sg

Marlow Industries China, II-VI
 Technologies Beijing
 A subsidiary of II-VI Incorporated
 Rm 202, 1# Lize 2nd Middle Road
 Wangjing, Chaoyang District
 Beijing 100102 China
 010-64398226 ext 105 (tel)
 010-64399315 (fax)
 info@iivibj.com