
(DEPE2270KA5N00)



## Film, Metallized PEN Stacked, Commercial Grade, LDE, 0.027 uF, 10%, 630 V, 200 V, 125C, 2824, 4mm



General Information		
Dielectric:	Metallized PEN Stacked	
Style:	SMD Chip	
Series:	LDE	
RoHS:	Yes	
Approvals:	AEC-Q200	
AEC-Q200:	Yes	

Dimensions	
Chip Size	2824
L	7.3mm +/-0.4mm
W	6.1mm +/-0.4mm
Т	4mm MAX
В	0.5mm +0.5/-0.3mm

Packaging Specifications	
Packaging:	T&R
Packaging Quantity:	1750

Specifications	
Capacitance:	0.027 uF
Capacitance Tolerance:	10%
Voltage DC:	630 VDC
Voltage AC:	200 V
Temperature Range:	-55/+125C
Rated Temperature:	125C
Dissipation Factor:	0.8% 1kHz
Insulation Resistance:	1 GOhms
Max dVdt:	100 V

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

