

## FEATURES

- High Efficiency & Long Life
- Wide Input Range for Worldwide use (up to 305Vac)
- Compact Size
- Optimized Performance
- Fully Isolated & SELV
- Protections: Short Circuit/ Open Circuit/ Over Voltage/ Over Temperature
- Class 2 power unit



## PRODUCT HIGHLIGHT

**Output Voltage/Current** 33W/1050mA  
:  
**Dimming:** 1-10V / PWM

## SPECIFICATION

<b>Model Name</b>	FSP30-ZZAP(105)M	
<b>Wattage</b>	33W	
<b>Case</b>	Plastic	
<b>IP Level</b>	IP20	
<b>Dimming</b>	1-10V / PWM Dimming	
<b>Input Electrical Specification</b>	<b>Input Voltage</b>	120~277 Vac
	<b>Input Frequency</b>	47~63 Hz
	<b>PFC</b>	≥0.9
	<b>Inrush Current</b>	<5A/5mS @ Cold start, 240Vac, Full load
<b>Constant Current / Constant Voltage</b>	Constant Current	
<b>Output Voltage and Current Rating</b>	<b>Output1</b>	14-32 V , 1050 mA
<b>Output Electrical Specification</b>	<b>Efficiency</b>	≥ 88 %
	<b>Life</b>	50.000 hours without system at full load and ambient 35°C @120Vac /240Vac
	<b>Protection Function</b>	OVP,OTP,SCP,OCP
<b>Environmental Requirement</b>	<b>TEMP. Range</b>	Operating : -20°C to +50°C Storage : -20°C to +85°C
	<b>Insulation</b>	Primary to Secondary: 500Vdc,25M ohms min.
<b>EMC performance</b>	<b>EN55015</b>	Class B Conducted, Class B radiated
	<b>EN61000-3-2</b>	B
	<b>EN61000-4-5</b>	Surge: ±2 KV common mode ± 1KV differential
<b>Dimension</b>	148mm(L) x 40mm(W)x 30mm(H)	

## PROTECTION FUNCTIONS

OVP,OTP,SCP,OCP

This content is subject to change, please refer to specification for more detail.  
FSP reserve the right to change the content without prior notice