

# ACP-2010MB / 2320MB

## 2U Rackmount Chassis for ATX/ MicroATX Motherboard with Low-Profile Rear Bracket Option



### Features


- LED indicators and audible alarm notification for system fault detection
- Shock-resistant drive bays to hold one 5.25" and three 3.5" drives for ACP-2010MB (one front-accessible and two internal); one slim optical disk drive, two internal 3.5" drives and dual mobile SAS/SATA HDD trays for ACP-2320MB
- Various riser card options to support three full-size PCI or PCIe cards for expansion
- Supports 300W / 400W ATX PFC power supply
- Reusable and washable air filters



### Specifications


		Front-accessible	Internal
Drive Bay	Slim Optical Disk Drive	- / 1	-
	5.25"	1 / 0	-
	3.5"	1 / 2 SAS/SATA HDD (mobile trays compatible with 2.5" HDD/SSD)	2 / 2
Cooling	Fan	2 (8 cm /47 CFM each) / 2 (8 cm /47 CFM each) + 1 (6 cm /28 CFM) for SAS/SATA storage unit	
	Air Filters	Yes	
Front I/O Interface	USB	2	
	PS/2	1	
Miscellaneous	LED Indicators	Power, HDD, temperature, fan	
	Rear Panel	Two 9-pin D-Sub openings	
Environment	Temperature	Operating 0 ~ 40° C (32 ~ 104° F)	Non-operating -20 ~ 60° C (-4 ~ 140° F)
	Humidity	10 ~ 85% @ 40° C, non-condensing	
	Vibration (5 ~ 500 Hz)	1 Grms	
	Shock	10 G (with 11 ms duration, half sine wave)	
		30 G	
Physical Characteristics	Dimensions (W x H x D)	482 x 88 x 480 mm (19" x 3.46" x 18.9")	
	Weight	10.7 kg (23.5 lb) / 11.7 kg (25.7 lb)	

### Front View




ACP-2010MB

### Inside View




ACP-2010MB

### Rear View



ACP-2320MB



ACP-2320MB


Rear I/O bracket for low profile add-on cards




## Dimensions

Unit: mm [inch]

### ACP-2010MB



### ACP-2320MB



## Ordering Information

Part Number	Power Supply
ACP-2010MB0-00XBE	Without power supply, with ATX switch
ACP-2320MB0-00XBE	Without power supply, with ATX switch

## Power Supply Options

(For detailed power supply specs, please refer to Chapter 13)

Part Number	Specifications	
	Watts	Input
1757000007G (ATX, PFC)	300W	AC 100 ~ 240 V (full range)
1757000105G (ATX, PFC)	400W	AC 100 ~ 240 V (full range)
1757001137 (ATX, PFC) (1+1 redundant)	250W	AC 100 ~ 240 V (full range)

## Optional Accessories

Part Number	Description
<b>Rear I/O panel kit for low-profile add-on cards</b>	
1939000361	Screw (should purchase 7 pcs)
1960034816N000	I/O bracket (should purchase 7 pcs)
1960019475T201	Rear panel for low-profile
1950014302N001	Special bracket for riser card AIMB-RP3P8-12A1E
96CB-SATAPOWER-6P1	SATA power wire 6-pin to big 4-pin (for slim ODD)
IDT-3120E	Mobile rack for converting a 3.5" drive bay to dual 2.5" SATA HDD trays

## Spare Parts

Part Number	Description
9662132020E	Black mobile HDD tray
1990007986S000	Door filter 156 x 45 x 5 mm
1990001949	Fan filter bracket 168 x 58 mm